



U.S. Patents: 6,744,259, 6,515,484.

HYAMP® III



Production Line Ground Bond Testers

Designed to thoroughly check the integrity of a safety ground circuit

Model 3130

30 Amp Ground Bond Tester

Model 3140

40 Amp Ground Bond Tester

Model 3160

60 Amp Ground Bond Tester

Features and Benefits

- Patented VERI-CHEK® feature prompts users through steps to validate the instrument's operation
- Graphic LCD provides intuitive menu system to simplify the entire testing process from set-up to results
- Patented CAL-ALERT® feature alerts the operator that the tester is due for re-calibration
- PLC Remote Control allows operators to remotely control the Ground Bond tester
- 10 Memories with 3 Steps per memory for storing and recalling test parameters
- Interconnects with an Associated Research Hipot tester to form a complete test system
- 4 wire measurement and milliohm offset for accurate Ground Bond test results
- Electronic Dwell timer for more consistent and reliable testing



Input Specifications

Voltage	115/230 VAC ± 10%, user selectable
Frequency	50/60 Hz ± 5%
Fuse - 3130	6.3 A, slo-blow 250 VAC
Fuse - 3140	10 A, slo-blow 250 VAC
Fuse - 3160	15 A, slo-blow 250 VAC

Ground Bond Test Mode

Output Rating	Current 3130: 1.00 - 30.00 A AC Voltage 3130: 6 V AC, fixed Current 3140: 1.00 - 40.00 A AC Voltage 3140: 8 V AC, fixed Current 3160: 1.00 - 60.00 A AC Voltage 3160: 9 V AC, fixed Resolution: 0.01 A Regulation: ± (2% of setting + 0.02 A)
Output Frequency	Range: 50 / 60 HZ, User Selectable
Dwell Time Setting	Range: 0 and 0.5 - 999.9 secs 0 for continuous running Resolution: 0.1 sec Accuracy: ± (0.1% of setting + 0.05 secs)
Maximum & Minimum Limits	Range 3130: 0 - 120 mΩ for 1 - 30.00 A 0 - 510 mΩ for 1 - 10.00 A Accuracy 3130: ± (2% of setting + 2 mΩ) Range 3140: 0 - 150 mΩ for 30.01 - 40.00 A 0 - 200 mΩ for 10.01 - 30.00 A 0 - 600 mΩ for 1.00 - 10.00 A Accuracy 3140: ± (3% of setting + 3 mΩ) Range 3160: 0 - 150 mΩ for 30.01 - 60.00 A 0 - 300 mΩ for 15.01 - 30.00 A 0 - 600 mΩ for 6.00 - 15.00 A Accuracy: ± (3% of setting + 3 mΩ)
Offset Capability	Range: 0 - 100 mΩ Resolution: 1 mΩ Accuracy: ± (2% of setting + 2 mΩ)
Current Display 3130	Range: 0.00 - 30.00 A Resolution: 0.01 A / step Accuracy: ± (2% of reading + 0.02 A)
Current Display 3140	Range: 0.00 - 40.00 A Resolution: 0.01 A Accuracy: ± (3% of reading + 0.03 A)
Current Display 3160	Range: 0.00 - 60.00 A Resolution: 0.01 A Accuracy: ± (3% of reading + 0.03 A)
Ohmmeter Display 3130	Range: 0 - 510 mΩ Resolution: 1 mΩ / step Accuracy: ± (2% of reading + 0.02 A)
Ohmmeter Display 3140	Range: 0 - 150 mΩ for 30.01 - 40.00 A 0 - 200 mΩ for 10.01 - 30.00 A 0 - 600 mΩ for 6.00 - 10.00 A Resolution: 1 mΩ Accuracy: ± (2% of reading + 2 mΩ) Range: 0 - 600 mΩ for 1.00 - 5.99 A Resolution: 1 mΩ Accuracy: ± (3% of reading + 3 mΩ)

Ground Bond Test Mode (Continued)

Ohmmeter Display 3160	Range: 0 - 150 mΩ for 30.01 - 60.00 A 0 - 300 mΩ for 15.01 - 30.00 A 0 - 600 mΩ for 6.00 - 15.00 A Resolution: 1 mΩ Accuracy: ± (2% of reading + 2 mΩ) Range: 0 - 600 mΩ for 1.00 - 5.99 A Resolution: 1 mΩ Accuracy: ± (3% of reading + 3 mΩ)
Timer Display	Range: 0.0 - 999.9 secs Resolution: 0.1 secs Accuracy: ± (0.1% of reading + 0.05 secs)

General Specifications

Remote Control & Signal Output	The following input and output signals are provided through two 9 pin D type connectors: 1. Remote control: Test, Reset, Interlock, and Withstand Processing 2. Remote recall of memory program #1, #2, and #3 3. Outputs: Pass, Fail, Test-in-process, Start Out and Reset Out
Program Memory	10 Memories, 3 steps per memory.
Security	Key Lock capability to avoid unauthorized access to all test parameters and memory locations.
Mechanical	Bench or rack mount with tilt up feet.
Dimensions 3130	(W x H x D) 8.5 x 4.0 x 15.5 in. (216 x 103 x 390 mm) includes feet
Dimensions 3140	(W x H x D) 8.5 x 4.0 x 16.9 in. (216 x 103 x 430 mm) includes feet
Dimensions 3160	(W x H x D) 16.9 x 5.1 x 15.7 in. (430 x 130 x 400 mm) includes feet
Weight 3130	19.15 lbs (8.7 kgs)
Weight 3140	30.9 lbs (14 kgs)
Weight 3160	49.40 lbs (22.40 kgs)
Calibration	Traceable to National Institute of Standards & Technology (NIST). Calibration controlled by software. Adjustments are made through front panel keypad in a restricted access calibration mode. Calibration information stored in non-volatile memory.

Available Accessories

Probe (38084)	Fixed tip 4-wire Ground Bond probe for use with the 3130.
Probe (38538)	Fixed tip 4-wire Ground Bond probe for use with the 3140.

Specifications subject to change without notice.

Cal Power

ASSOCIATED RESEARCH, INC.®



- Customer support & technical services
- 5-Year extended warranty*
- 24-Hour turn-around on calibrations
- Industry seminars, expert training & education programs
- Local sales offices throughout the world

*With annual calibration from Associated Research.

CalPower Srl
Via Acquana, 29 C22100 COMO CITALY
Tel.: +39-031526566 CFax: +39-031507984
E-Mail: info@calpower.it Chttp://www.calpower.it

CAI technical modifications reserved. Without engagement

