



**Bagno ad acqua con microprocessore
Water Bath with microprocessor**

per laboratori—for Laboratories



<i>Features</i>
Accurate Microprocessor Control
Three User-defined
Temperature Preset Buttons
Redundant Safety Backup
Front Panel Lockout
Electronic Calibration

PolyScience Water Baths offer superior temperature control, range, and uniformity. Bath fluids can be controlled at temperatures as high as 100°C (60°C without cover) with 0.1°C precision and +/-0.2°C uniformity. Bath temperature is displayed continuously on a bright, easy-to-read LED panel in your choice of °C or °F. Set point temperature is recalled with just the touch of a button. Three user-defined temperature preset buttons allow for quick selection of often used temperature set points. Dual thermostats provide optimum protection for your work and water bath. The high limit alarm alerts you if bath temperature exceeds your pre-set limit. A secondary Safety Set thermostat guards against thermal runaway, automatically disconnecting heater power should bath temperature get too high or the liquid level drop too low.

Capacity	Overall Dimensions L x W x H	Opening Dimensions L x W x H	Shipping Weight	Volts, Hz, Amps	Cat. No.
2 Liter	8.94 x 7.90 x 8.13 in 22.71 x 20.07 x 20.65 cm	5.31 x 5.88 x 5.81 in 13.49 x 14.94 x 14.76 cm	11 lbs 4.99 kg	120V, 60Hz, 2.5A 240V, 50Hz, 1.25A	WD02A11B WD02A12E
2 Liter Shallow	9.44 x 13.65 x 8.13 in 23.98 x 34.67 x 20.65 cm	5.81 x 11.69 x 2.50 in 14.76 x 29.69 x 6.35 cm	12 lbs 5.44 kg	120V, 60Hz, 2.5A 240V, 50Hz, 1.25A	WD2SA11B WD2SA12E
5 Liter	9.44 x 13.65 x 8.13 in 23.98 x 34.67 x 20.65 cm	5.94 x 11.75 x 5.94 in 15.09 x 29.85 x 15.09 cm	15 lbs 6.80 kg	120V, 60Hz, 4.2A 240V, 50Hz, 2.1A	WD05A11B WD05A12E
10 Liter	15.43 x 14.90 x 8.13 in 39.19 x 37.85 x 20.65 cm	11.69 x 12.75 x 5.94 in 29.69 x 32.39 x 15.09 cm	23 lbs 10.43 kg	120V, 60Hz, 4.2A 240V, 50Hz, 2.1A	WD10A11B WD10A12E
20 Liter	15.19 x 21.65 x 8.13 in 38.58 x 54.99 x 20.65 cm	11.50 x 19.50 x 5.88 in 29.21 x 49.53 x 14.94 cm	30 lbs 13.61 kg	120V, 60Hz, 8.3A 240V, 50Hz, 4.15A	WD20A11B WD20A12E
28 Liter	15.19 x 21.65 x 10.13 in 38.58 x 54.99 x 25.73 cm	11.63 x 19.56 x 7.94 in 29.54 x 49.68 x 20.17 cm	33 lbs 14.97 kg	120V, 60Hz, 8.3A 240V, 50Hz, 4.15A	WD28A11B WD28A12E

Via Acquanera, 29
22100 Como
tel 031 526566—fax 031 507984
Email : info@calpower.it
Website : www.caltower.it