Looking For A High Power, Low Profile Power Supply?

KEPCO

Will Point You In The Right Direction!





You'll Always Find What You Need At Kepco



KEPCO SERIES KLN - High Power, Low Profile, Many Models

The Kepco Series KLN is a new family of automatic crossover, low-profile, high-performance, low-cost programmable power supplies. The KLN Series offers stable d-c power in a 1U high, half-rack package for 750W, a 1U high, full-rack package for 1500W and a 2U high, full-rack package for 3000W. A total of 39 voltage-current combinations are offered. Output voltages range from 0-6 Volts to 0-600 Volts and output currents range from 0-400 Amps down to 0-1.25 Amps. Speed-controlled fans limit acoustic noise for bench-top applications when full power is not needed.

Precise programming of voltage, current and their limits may be achieved from the front panel, or by analog means or by RS 485 digital control. GPIB or LAN interfaces are factory-installed options.

For more information visit

www.kepcopower.com/kln.htm

3

MARKETS AND APPLICATIONS

- Aerospace and Satellite Test
- Telecom and IT Industry
- Automated Test Equipment
- Factory Automation
- QC Testing
- Burn-in
- Solar
- Water Purification
- Thermal Process Control
- Chemical Processing
- Semiconductor Manufacturing
- Battery Charging and Testing
- Electroplating, Sputtering and Coating
- New Energy R&D



Data subject to change without notice. © 2013 KEPCO, INC. Litho in USA

KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11355 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102 Email: hq@kepcopower.com • www.kepcopower.com



If you are looking for a high resolution (16 bit D/A for setting of voltage and current, 24 bit A/D for measurement), stable, quiet (speed-controlled fan) d-c power supply for your rack or bench, **choose the 750W Series KLN.**



KLN 750 WATT MODEL TABLE

MODEL	D-C OUTP	UT RANGE	RIPPLE ⁽³⁾		LINE REGULATION (5) (11)		LOAD REGULATION (11)		RESPONSE TIME (7)		(7)	REMOTE
	CV (1)	CC ⁽²⁾	CV	CC ⁽⁴⁾	CV	CC	CV ⁽⁶⁾	CC (6)	FULL LOAD UP	FULL LOAD DOWN	NO LOAD DOWN	VOLTAGE DROP (max)
	V d-c	A d-c	mV rms	mA rms	0.05% +mV	0.1% +mA	0.05% +mV	0.1% +mA	Sec	Sec	Sec	V
KLN 6-100	0-6	0-100	10	180	2.8	11	2.8	23	0.08	0.05	0.6	1
KLN 8-90	0-8	0-90	10	180	2.8	11	2.8	23	0.08	0.05	0.6	1
KLN 12.5-60	0-12.5	0-60	10	120	4	8.5	4	18	0.08	0.05	0.8	1
KLN 20-38	0-20	0-38	10	76	4	5.8	4	12.6	0.08	0.05	0.8	1
KLN 30-25	0-30	0-25	10	63	5	4.5	5	10	0.08	0.08	0.9	1.5
KLN 40-19	0-40	0-19	10	48	6	3.9	6	8.8	0.08	0.08	1	2
KLN 50-15	0-50	0-15	10	43	8	3.6	8	8.2	0.08	0.08	1.1	2
KLN 60-12.5	0-60	0-12.5	10	38	8	3.25	8	7.5	0.08	0.08	1.1	3
KLN 80-9.5	0-80	0-9.5	10	29	10	2.95	10	6.9	0.15	0.15	1.2	4
KLN 100-7.5	0-100	0-7.5	10	23	12	2.75	12	6.5	0.15	0.15	1.5	5
KLN 150-5	0-150	0-5	16	18	17	2.5	17	6	0.15	0.15	2	5
KLN 300-2.5	0-300	0-2.5	25	13	32	2.25	32	5.5	0.15	0.15	3	5
KLN 600-1.25	0-600	0-1.25	75	8	62	2.13	62	5.26	0.25	0.3	4	5

(1) Actual output voltage is $\leq 0.1\%$ of rated voltage when output voltage is set to zero.

(2) Actual output current is ≤0.2% of the rated current when output current is set to zero (resistive load).

(3) Measured when output is within 10%-100% of rated value; ripple bandwidth: 300kHz (rms), noise bandwidth: <20MHz (p-p).

(4) For 6V model: measured when output voltage 2-6V and rated current; all other models measured when output 10-100% of rated voltage and rated current.

(5) Input voltage 100~240V a-c 50/60Hz, constant load.

(6) Constant input voltage and output from no load to full load.

(7) With rated input, resistive load output voltage changes from 10% to 90% or from 90% to 10%.

(8) Rated power output with input 115V or 230V a-c

(9) Specifications met after 30 minutes of operation, ambient temperature 23±5°C, humidity under 80% R. H,

a-c input voltage nominal ±5% of nominal, THD is 2%, not using the remote compensation, not operating in series or parallel.

(10) Add G suffix for models with optional GPIB interface, add E suffix for optional LAN interface.

(11) For example, the spec for KLN 6-100 line regulation and load regulation in CV mode is 0.05% + 2.8mV (or 6 x 0.0005 = +3mV + 2.8mV = 5.8mV).

1500 WATTS

If you are looking for a full rack, 1U, 1500 Watt d-c power supply which runs cool in your rack (with no air gap required between units) or on your bench, **choose the 1500W Series KLN.**



KLN 1500 WATT MODEL TABLE												
MODEL	D-C OUTP	UT RANGE	RIPP	LE ⁽³⁾	LINE REGUL	ation ^{(5) (11)}	LOAD REGI	JLATION ⁽¹¹⁾	RE	SPONSE TIME	(7)	REMOTE
(6) (9) (10)	CV (1)	CC (2)	CV	CC ⁽⁴⁾	CV	CC	CV (6)	CC (6)	FULL LOAD UP	FULL LOAD DOWN	NO LOAD DOWN	VOLTAGE DROP (max)
	V d-c	A d-c	mV rms	mA rms	0.05% +mV	0.1% +mA	0.05% +mV	0.1% +mA	Sec	Sec	Sec	V
KLN 6-200	0-6	0-200	15	360	2.8	18.5	2.8	38	0.08	0.05	0.6	1
KLN 8-180	0-8	0-180	15	360	2.8	18.5	2.8	38	0.08	0.05	0.6	1
KLN 12.5-120	0-12.5	0-120	15	248	3.4	14.5	4	28	0.08	0.05	0.8	1
KLN 20-76	0-20	0-76	15	152	4	9.6	4	20.2	0.08	0.05	0.8	1
KLN 30-50	0-30	0-50	15	125	5	7	5	15	0.08	0.08	0.9	1.5
KLN 40-38	0-40	0-38	15	95	6	5.8	6	12.6	0.08	0.08	1	2
KLN 50-30	0-50	0-30	15	85	7	5.2	7	11.4	0.08	0.08	1.1	2
KLN 60-25	0-60	0-25	15	75	8	4.5	8	10	0.08	0.08	1.1	3
KLN 80-19	0-80	0-19	15	57	10	3.9	10	8.8	0.15	0.15	1.2	4
KLN 100-15	0-100	0-15	15	45	12	3.5	12	8	0.15	0.15	1.5	5
KLN 150-10	0-150	0-10	24	45	12	3.5	12	8	0.15	0.15	2	5
KLN 300-5	0-300	0-5	38	25	32	2.5	32	6	0.15	0.15	3	5
KLN 600-2.5	0-600	0-2.5	113	15	62	2.26	62	5.5	0.25	0.3	4	5

See footnotes on 750 Watt Model Table, page 3.



KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11355 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102 Email: hq@kepcopower.com • **www.kepcopower.com**

3000 WATTS

If you are looking for a 3000 Watt programmable d-c power supply that operates on single phase input with active PFC meeting EN 61000-3-2:2006 Class A standards, **choose the 3000W Series KLN.**



Front View 2U High



KLN 3000 WATT MODEL TABLE												
MODEL	D-C OUTP	UT RANGE	RIPP	PLE ⁽³⁾	LINE REGUL	ation ^{(5) (11)}	LOAD REGU	JLATION ⁽¹¹⁾	RE	SPONSE TIME	(7)	REMOTE
(8) (9) (10)	CV (1)	CC ⁽²⁾	CV	CC ⁽⁴⁾	CV	CC	CV (6)	CC (6)	FULL LOAD UP	FULL LOAD DOWN	NO LOAD DOWN	VOLTAGE DROP (max)
	V d-c	A d-c	mV rms	mA rms	0.05% +mV	0.1% +mA	0.05% +mV	0.1% +mA	Sec	Sec	Sec	V
KLN 6-400	0-6	0-400	23	1000	2.8	42	6.2	85	0.08	0.02	0.5	1
KLN 8-360	0-8	0-360	23	1000	2.8	42	6.2	85	0.08	0.02	0.5	1
KLN 12.5-240	0-12.5	0-240	23	800	3.2	29	7.1	60	0.08	0.1	0.8	1
KLN 20-150	0-20	0-150	23	600	4	18.5	8	38	0.08	0.1	0.8	1
KLN 30-100	0-30	0-100	23	310	5	13	9.5	27	0.08	0.16	0.9	1.5
KLN 40-76	0-40	0-76	23	250	6	10.5	11	22	0.08	0.16	1	2
KLN 50-60	0-50	0-60	23	200	7	9	13	19	0.08	0.16	1.1	2
KLN 60-50	0-60	0-50	23	150	8	7.5	14	16	0.08	0.16	1.1	3
KLN 80-38	0-80	0-38	23	110	10	6.2	17	13.4	0.15	0.3	1.2	4
KLN 100-30	0-100	0-30	23	90	12	5.3	20	11.6	0.15	0.3	1.5	5
KLN 150-20	0-150	0-20	36	90	17	4.2	27.5	9.4	0.15	0.3	2	5
KLN 300-10	0-300	0-10	57	50	32	3.1	50	7.2	0.15	0.3	3.5	5
KLN 600-5	0-600	0-5	170	30	62	2.55	95	6.1	0.25	0.5	4	5

(5) Input voltage: 190-240V a-c. 50/60Hz, constant load.

For others, see footnotes on 750 Watt Model Table, page 3.

KLN INPUT SPECIFICATIONS

SPECIFICATION		RATING/DESCRIPTION		
Input Voltage	750 & 1500 Watt	100-240Vac, 50/60Hz		
	3000 Watt	190-240Vac, 50/60Hz		
Input Current (Full load)	750 Watt	8.1A@115V a-c; 4.1A@230V a-c		
	1500 Watt	16.2A@115V a-c; 8.1A@230V a-c		
	3000 Watt	15.6A@230V a-c		
Inrush Current	750 Watt	12.5A@230V a-c		
	1500 Watt	25A@230V a-c		
	3000 Watt	50A@230V a-c		
Power Factor (PF)	750 & 1500 Watt	0.99 (at 115V a-c, rated output)		
lypical	3000 Watt	0.99 (at 230V a-c, rated output)		
Efficiency	750 Watt	76% - 87%		
	1500 Watt	77% - 88%		
	3000 Watt	82% - 88%		
Isolation Voltage	Input-Outputs	2000V a-c: 1 minute		
	Input-Ground	2000V a-c: 1 minute		
	Output-Ground (6V-150V)	350V d-c, leakage current: 100µA		
	Output-Ground (300V-600V)	1200V d-c, leakage current: 100µA		

KLN OUTPUT SPECIFICATIONS					
SPECIFICATION			RATING/DESCRIPTION		
Type of Stabilizer			Constant Voltage (CV)/Constant Current (CC), automatic crossover		
Adjustment Rang	е	Voltage	0 to 100% of rated voltage		
		Current	0 to 100% of rated current		
Protective Function	ons		Programmable overvoltage (OVP) Programmable overcurrent (OCP) Overtemperature (OTP) Fuse blown		
Protection Setting)	Overvoltage	0% to 110% of rated voltage		
Range		Overcurrent	0% to 110% of rated current		
Remote Error Se	nse Corr	pensation	5V max. (See Applicable Model Table)		
Parallel Operation	ı		Up to 5 units maximum, automatic load sharing		
Series Operation			2 units maximum (total voltage must not exceed 600V)		
Temperature, Coefficient	Const Const	tant Voltage Mode ant Current Mode	100ppm/°C of rated output voltage or current, after 30 minute warm-up		
Time Drift Constant Voltage Mode Constant Current Mode		tant Voltage Mode ant Current Mode	0.05% of rated output voltage or current over 8 hrs interval following 30 minutes warm-up. Constant line, load and temperature.		
Transient	Transient Constant Voltage Mode		20V and under: ≤1.5ms;		
			30V-100V: ≤1ms		
			150V-600V: ≤2ms		



Parallel connection of two identical KLN power supplies (up to five possible) using optional Parallel Socket Board 536-0129 and Programming Port Cable 518-0119



Series connection of two identical KLN power supplies using optional Series Socket Board 536-0130 and Programming Port Cable 518-0119



KLN PROGRAMMING CHARACTERISTICS - LOCAL

SPECIFICATION		RATING/DESCRIPTION
Local Control		Rotary encoder
Setting Resolution	Voltage & Current	4 digits
Display Resolution	Voltage & Current	4 digits
Setting Accuracy	Voltage	$\pm 0.1\% \pm 3C^{(1)}$ at rated voltage
	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current
Display Reading	Voltage	$\pm 0.2\% \pm 3C^{(1)}$ at rated voltage
Accuracy	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current
Overvoltage Protection		Programmable, 0 to 110% of rated voltage
Overcurrent Protection		Programmable, 0 to 110% of rated current

(1) C = 1 count of the last displayed digit.

KLN PROGRAMMING CHARACTERISTICS - DIGITAL

SPECIFICATION		RATING/DESCRIPTION
Command Setting Resolution		±0.002% of full scale
Command Readback Resolution		±0.002% of full scale
Command and D/A	Voltage	$\pm 0.1\% \pm 3C^{(1)}$ at rated voltage
Setting Accuracy	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current
Command and A/D Measurement Accuracy	Voltage	$\pm 0.2\% \pm 2C^{(1)}$ at rated voltage (Average Measurement)
	Current	$\pm 0.5\% \pm 3C^{(1)}$ at rated current (Average Measurement)
Command Response Time		≤20ms (After received) ⁽²⁾
RS-485 Digital Interface (Standard)		Default baud rate: 115.2K Baud rates: 4.8K, 9.6K, 19.2K, 38.4K, 57.6K, 115.2K user selectable Max number of units connected to bus: 254 Max. effective control distance: 1000 meters
GPIB IEEE 488.2 Digital Interface		Optional (G suffix)
LAN Digital Interface		Optional (E suffix)



Analog Interface RS 485 Interface (Standard)



LAN Interface (Optional) Added



GPIB (IEEE 488) Interface (Optional) Added

(1) C = 1 count of the last displayed digit.

(2) Programming time = Command response time + Output response time. The output response time differs for different models, from 30mS ~ 200mS.

KLN PROGRAMMING CHARACTERISTICS - ANALOG						
SPECIFICATION		RATING/DESCRIPTION				
Analog Setting Accuracy Constant Voltage Mode (CV) Current		± 5% ± 5%				
Analog Setting Accura Constant Current Mode (CC)	acy Voltage	± 5% ± 5%				
Analog Monitor	Rated voltage output	10.00V ± 0.25V				
, local aby	Zero voltage output Rated current output	0.00V ± 0.25V 10.00V ± 0.25V				
	Zero current output	0.00V ± 0.25V				

KLN PHYSICAL SPECIFICATIONS					
SPECIFICATION			RATING/DESCRIPTION		
Weight		750 Watt	11.2 lbs (5.1 Kg)		
		1500 Watt	20.3 lbs (9.2 Kg)		
		3000 Watt	33.2 lbs (15.1 Kg)		
Dimensions W x H x D		750 Watt	8.46" x 1.73" x 18.5" (215mm x 44mm x 470mm)		
		1500 Watt	16.93" x 1.73" x 18.5" (430mm x 44mm x 470mm)		
		3000 Watt	16.93" x 3.46" x 18.5" (430mm x 88mm x 470mm)		
Source Power		750 Watt	IEC 320 inlet		
Connector	1500 & 3000 Watt		3-position terminal block		
Load	6V to 10	0V models	± bus bars with protective cover		
Connections	150V to 60	0V models	(750W) 5-position Euroblock		
	150V to 60	0V models	(1500W & 3000W) 4-position terminal block		
Programming C	ontrol port		26-pin connector (mating connector supplied)		
SER IN port			2-position Euroblock (mating connector supplied)		
Sense port			3-position Euroblock (mating connector supplied)		
RS-485 port		3-position Euroblock (mating connector supplied)			
LAN port (option	nal)		RJ 45 connector		
GPIB port (optio	onal)		Standard IEEE 488.2 GPIB connector		

KLN GENERAL (ENVIRONMENTAL) SPECIFICATIONS

SPECIFICATION			RATING/DESCRIPTION		
Temperature		Operating	0 to 50°C (indoor use)		
		Storage	-20 to +70°C		
Humidity		Operating	30%~90% RH (no condensation)		
		Storage	10%~90% RH (no condensation)		
Altitude			3000m max		
Cooling			Speed-Controlled Fan		
Acoustic Noise			<70 dB (A)		
EMC Emissions	Conducted	Disturbance	EN 55011:2007 + A2:2007 Class B		
(EN 61326-1)	Radiated	Disturbance	EN 55011:2007 + A2:2007 Class B		
	Harmonic Distortion		EN 61000-3-2:2006 Class A		
	Voltage	Fluctuations and Flicker	EN 61000-3-3:2008 Section 5		
EMC Immunity	Electrostat	tic Discharge (ESD)	EN 61000-4-2:2009 Class B		
(EN 61326-1)	F Ma	Radiated RF agnetic Field	EN 61000-4-3:2006 + A1:2008 + A2:2010 Class A		
	El Transients	ectrical Fast and Bursts	EN 61000-4-4:2004 + A1:2010 Class B		
		Surge	EN 61000-4-5:2006 Class B		
	Conducted Induced b	Disturbance by RF Fields	EN 61000-4-6:2009, Class A		
	Volta Short I	ge Dips and nterruptions	EN 61000-4-11:2004, Class C		

NOTE: All specifications apply after power on for 30 minutes, ambient temperature: $23\pm5^{\circ}C$, Humidity: under 80% RH, AC Voltage: $\pm5\%$, Frequency: $\pm5\%$.

For more information visit www.kepcopower.com/kln.htm

Looking For More High Power, Low Profile Power Supplies?



SERIES KLR

Kepco introduces Series KLR, offering 2400 Watts of stable, controllable d-c power in the industry standard 1U package. Five models from 20 Volts to 300 Volts are available with a conventional rectangular operating area. Input is 185-264V a-c, single phase. GPIB, RS232 and isolated analog programming are all standard, LXI Ethernet is a factory installed option replacing RS232.

www.kepcopower.com/klr.htm



SERIES KLP

Using high-frequency switch-mode topology for high efficiency and small size, the KLP provides 1200 watts of well-regulated, controllable d-c power in a 1U (1.75 inch high) by 19 inch rack-mountable package. KLP replaces the need for multiple power supplies by expanding the operating region. The breakthrough of a hyperbolic power limit delivers a full 1200 Watts over an expanded operating range, not just the conventional rectangular operating area.

www.kepcopower.com/klp.htm





KEPCO, INC. • 131-38 Sanford Avenue • Flushing, NY 11355 USA • Tel: (718) 461-7000 • Fax: (718) 767-1102 Email: hq@kepcopower.com • www.kepcopower.com

Via Acquanera, 29 tel. 031.526.566 (r.a.) info@calpower.it 22100 COM0 fax 031.507.984 www.calpower.it