

Cal Power

Via Acquanera, 29 22100 COMO
tel. 031.526.566 (r.a.) fax 031.507.984
info@calpower.it www.caltower.it



Instruments for Electrical Safety Compliance Testing



Safety Is Our Only Focus®

Hipot • Ground Bond • Insulation Resistance • Leakage Current • Functional Run
Medical Test Systems • HV/HC Multiplexers • Software Solutions

LONGEVITY FROM LEADERSHIP

For over 80 years we have shaped the electrical safety compliance industry with **innovative** test and measurement solutions. We strive to improve all aspects of the electrical safety testing process for our customers through **dedication** to product quality and our **commitment** to customer satisfaction. Since being incorporated in 1936 we have remained family owned and continue to make business decisions with the **values** of our founder in mind. We are devoted to building lasting relationships with our loyal customers, who lead the manufacturing industry around the world.



We back every AR instrument with an industry-leading 3 year warranty. Choose us for your annual calibration needs and we'll **extend your warranty** at no additional cost for up to 5 years from the date of purchase.



All products are shipped from our factory within **1 business day**, guaranteed. If your order ships late, we pay the freight.



If for ANY reason you're not **completely satisfied** with your experience, you can simply return your instrument within 45 days of purchase for a full refund.



A HISTORY OF INNOVATION

1936 Associated Research was founded.

1939 We introduced the first battery operated Megohmmeter, the Vibrotest, in the United States.

1966 We commenced the first Cable Testing/Fault Location school known as ARU. ARU continued for over 25 years.

1993 We introduced the first complete family of microprocessor-controlled electrical safety instruments.

1995 We developed the first multi-function electrical safety compliance analyzer.

1997 We released the first electrical safety instrument with a built-in multiplexer for multi-point testing.

1999 We introduced Autoware, the first software package for automated instrument control, in the EST industry.

2001 We released our patented safety feature, SmartGFI®, to provide our customers with maximum operator protection during high voltage testing.

2012 We launched the first electrical safety compliance analyzer with a built-in AC power source.

2013 We developed the first mobile app in the electrical safety testing industry.

2017 We launched the Applications Consulting program.

OUR MISSION

We build relationships with manufacturers around the globe who trust our products and expertise in electrical safety compliance testing to protect their employees and customers from the dangers of electricity.

FOCUSED ON EDUCATION

With over 80 years of industry experience, we have the resources and expertise to assist you with your educational needs throughout the life of your product.

- Quick Start Videos
- Quick Start Guides
- Monthly Webinars
- White Papers & Articles
- Live Web Demos
- On-Site Training

SOCIAL RESPONSIBILITY

We believe that people and organizations must behave ethically and with sensitivity toward cultural, economic and environmental issues.

GREEN INITIATIVE

We are committed to responsible manufacturing processes and environmental sustainability. Our Green Initiative is led by decision makers from all departments who are tasked with making day-to-day operations as green as possible.



SERVING THE COMMUNITY

Proud Sponsor of



We donate a portion of our profits to raising awareness about the dangers of electricity.



We host and support annual food drives to better serve our local community.

PRODUCT REFERENCE CHART



AC Hipot



DC Hipot



Ground Bond



Ground Continuity



Insulation Resistance



Leakage Current



Functional Run



Built-in AC Power

Hypot®

3805	•			•	
3865	•	•		•	
3870	•	•		•	•

HypotULTRA®

7800	500 VA	•		•	•
7804	•	•	•	•	•
7820	•			•	
7850	•	•		•	•
7854	500 VA	•	•	•	•

OMNIA® II

8204	•	•	•	•	•		
8254	500 VA	•	•	•	•		
8206	•	•	•	•	•	•	•
8256	500 VA	•	•	•	•	•	•
8207	•	•	•	•	•	•	•
8257	500 VA	•	•	•	•	•	•

HYAMP®

3240	•
------	---

HypotMAX®

7705	•
7710	•
7715	•
7720	•

LINECHEK® II

620L	•	•
------	---	---

Not sure which instrument is right for your application?

Use our product selection tool to identify the instrument that satisfies your testing requirements.

Go to [arisafety.com](https://www.arisafety.com) and follow the link to the **Product Selection Tool**.



USB



RS-232



Ethernet



GPIB

Internal
MultiplexerModular
MultiplexerAutware®3
CompatiblePower Source
Recommended**Hypot®**

3805 •

3865 •

3870 •

HypotULTRA®

7800 • • Opt. Opt. • •

7804 • • Opt. Opt. • •

7820 • • Opt. Opt. • • •

7850 • • Opt. Opt. • • •

7854 • • Opt. Opt. • •

OMNIA® II

8204 • • Opt. Opt. • • •

8254 • • Opt. Opt. • • •

8206 • • Opt. Opt. • • •

8256 • • Opt. Opt. • • •

8207 • • Opt. Opt. • •

8257 • • Opt. Opt. • •

HYAMP®

3240 •

HypotMAX®

7705 • • Opt.

7710 • • Opt.

7715 • • Opt.

7720 • • Opt.

LINECHEK® II

620L • • Opt. Opt. • • •

MedTEST is the most comprehensive Electrical Safety Compliance test system in the industry designed exclusively for medical applications. Customize it to meet your specific medical safety testing needs in order to comply with standards such as UL60601, IEC60601-1, EN60601-1, UL2601, and IEC601-1. See page 24 for more details.

Hypot®

Production Line Hipot Testing
at its Finest



Our new Hypot® Series raises the bar for production line Hipot testing. Improve traceability with on-board data storage and easily transfer test result data and test settings via convenient front panel USB. Take the guesswork out of your production line with the direct barcode connection to quickly associate products with pre-programmed test files. We've included advanced features like improved security and a touch screen interface that provides custom pop-up prompts displayed before each test step. We've dramatically reduced the weight and footprint of the Hypot® Series to make safety compliance a less strenuous ordeal. Quickly interconnect with the HYAMP® Series to form a complete safety compliance system.



Find the Model that Fits Your Testing Needs



AC Hipot



DC Hipot



Ground
Continuity



Insulation
Resistance

EN 50191
COMPLIANT

NEW 2017	3805	•		•	
NEW 2017	3865	•	•	•	•
NEW 2017	3870	•	•	•	•

AVAILABLE INTERFACES



USB

SAFETY & PRODUCTIVITY FEATURES



SmartGFI®
Automatic
operator shock
protection



**Remote Safety
Interlock**
Easily disable
HV output



Data Transfer
Easily import/
export test
files and data
via USB



**Barcode
Capability**
Direct barcode
connection



**Multiple
Languages**
Multi-Language
user interface



PLC Remote
Basic PLC
relay control



Prompt & Hold
Provides alerts
& instructions
between tests



**Advanced
User Security**
Customize ID
& password
protection



Interconnection
Interconnect with
HYAMP® to form
a complete test
system



Ramp-HI®
Reduce ramp
time during
DC Hipot



Charge-LO®
Confirms
proper DUT
connection



FailCHEK™
Confirms
failure
detection



**Accredited
Cal**
Accredited
calibration
options
available



My Menu
Customize your
own shortcut
menu



**On Board Data
Storage**
Save up to
1,500 Test
Results on-board

INPUT SPECIFICATIONS				
Voltage	100 – 120 VAC / 200 – 240 VAC ± 10% Auto Range			
Frequency	50/60 Hz ± 5%			
Fuse	3.15 A, Fast Blow 250 VAC			
DIELECTRIC WITHSTAND TEST MODE				
Output Rating	3805/3865/3870	5 kVA @ 20 mAAC 6 kVA @ 7.5 mADC (3865/3870 only)		
Maximum Limit	3805/3865/3870	AC	Range: Resolution:	0.00 – 20.00 mA 0.01 mA
		DC	Range: Resolution: Accuracy:	0 – 7500 µA 1 µA AC and DC ± (2% of setting + 2 counts)
Minimum Limit	3805/3865/3870	AC	Range: Resolution:	0.000 – 9.999 mA 0.001 mA
		DC	Range: Resolution: Accuracy:	0.0 – 999.9 µA 0.1µA AC and DC ± (2% of setting + 2 counts)
Arc Detection	Range:	1-9, ON/OFF Select		
Ground Fault Interrupt	GFI Trip Current: 450 µA max (AC or DC), Fixed			
	HV Shut Down Speed: < 1 msec			
Current Display	3805/3865/3870	AC	Range 1: Range 2:	0.000 – 4.000 mA 3.50 – 20.00 mA
		DC	Range 1: Range 2: Range 3:	0.0 µA – 400.0 µA 0.350 mA – 4.000 mA 3.50 mA – 7.50 mA
		Accuracy:		All Ranges ± (2% of reading + 2 counts)
DC Output Ripple	≤ 5% Ripple rms at 6 kVDC @ 7.5 mA Resistive Load			
RAMP-HI Selectable	Range: 0.0 – 7,500 µA, User Selectable			
Charge-LO	0 – 350 µA DC or Auto Set			
Discharge Time	< 50 msec for no load, < 100 msec for capacitive load The maximum capacitive load vs. output voltage: 1µF < 1KV 0.08µF < 4KV 0.75µF < 2KV 0.04µF < 5KV 0.5µF < 3KV 0.015uF < 6KV			
AC Voltage Waveform/ Frequency	Sine Wave, Crest Factor = 1.3 – 1.5			
	Range:	50 or 60 Hz, User Selectable		
Dwell Timer	Range:	AC 0, 0.2-999.9 sec (0=Continuous) DC 0, 0.4-999.9 sec (0=Continuous)		
Ramp Timer	Range:	Ramp-Up: 0.1 – 999.9 sec Ramp-Down: AC 0.0 – 999.9 sec DC 0, 1.0 – 999.9 sec, (0=OFF)		
Ground Continuity Current	DC 0.1A ± 0.01 A, fixed			
Ground Continuity Maximum Limit Minimum Limit	Range: Resolution: Accuracy:	0.00 – 1.50 Ω 0.01 Ω ± (3% of setting + 0.02 Ω)		
	Ground Continuity Auto Offset	Range: Resolution: Accuracy:	0.00 – 0.50 Ω 0.01 Ω ± (3% of setting + 0.02 Ω)	

INSULATION RESISTANCE TEST MODE				
Voltage Setting	Range: Resolution: Accuracy:	30 – 1,000 VDC 1 V ± (2% of setting + 5 V)		
Resistance Display	Range:	1 – 50,000 MΩ		
	Resolution:			
		30 – 99 VDC	100 – 499 VDC	500 – 1000 VDC
	MΩ	MΩ	MΩ	MΩ
	0.001	1.000 – 1.999	1.000 – 1.999	1.000 – 9.999
	0.01	2.00 – 19.99	2.00 – 19.99	10.00 – 99.99
	0.1	20.0 – 199.9	20.0 – 199.9	100.0 – 999.9
1	200 – 10,000	200 – 20,000	1000 – 50000	
	Accuracy:	± (8% of reading+2 counts) at test voltage 30 – 499 V and 1.00–999.9 MΩ		
	At test voltage 500-1000 V ± (2% of reading + 2 counts) for 1.00 – 999.9 MΩ ± (5% of reading + 2 counts) for 1000 – 9999 MΩ ± (15% of reading + 2 counts) for 10000 – 50,000 MΩ			
HI & LO-Limit	Range: Resolution:	0, 1.00 – 99.99 MΩ (0=OFF, HI-Limit ONLY) 0.01 MΩ 1000-50000 1 MΩ		
	Range: Resolution:	100.0 – 999.9 MΩ 0.1 MΩ		
	Accuracy:	At test voltage 500-1000 V ± (2% of setting + 2 counts) for 1.00 – 999.9 MΩ ± (5% of setting + 2 counts) for 1000 – 9999 MΩ ± (15% of setting + 2 counts) for 10000 – 50,000 MΩ		
Charge-LO	Range:	0.000 – 3.500 µA DC or Auto Set		
Ramp Timer	Range:	Ramp-Up: 0.1 – 999.9 sec Ramp-Down: 0, 1.0 – 999.9 sec, (0=OFF)		
Delay Timer	Range:	0.5 – 999.9 sec (0=OFF)		
Dwell Timer	Range:	0, 0.5 – 999.9 sec (0=continuous)		
GENERAL SPECIFICATIONS				
Remote Control and Signal I/O	Inputs: Test, Reset, Hardware Interlock, File Recall Outputs: Pass, Fail, Test-in-Process, Reset-Out, Start-Out			
Vmax	Displays the maximum voltage value recorded during a breakdown			
Imax	Displays the maximum leakage current value read during a test			
Memories	50 steps 1500 test results			
Interface	USB standard			
Language	English, Traditional Chinese, Simplified Chinese, Turkish, Portuguese, Spanish, German, French			
Security	Multiple user setups with ID and password			
Dimensions (W x H x D)	3805/3865/3870:	8.5" x 3.5" x 11.9" (215 mm x 88.1 mm x 300 mm)		
Weight	3805/3865/3870:	12 lbs (5.46 kgs)		

Why We Use Counts

Associated Research publishes some specifications using "counts" which allows us to provide a better indication of the instrument's capabilities across measurement ranges. A count refers to the lowest resolution of the display for a given measurement range. For example, if the resolution for voltage is 1V then 2 counts = 2 V.

Specifications subject to change without notice.

HypotULTRA®

The Most Flexible and Feature-Rich Automated Dielectric Analyzer Available



Our new HypotULTRA® models provide all the tools you need to modernize your production line with best-in-class 4-in-1 test capability and a slim 2U design. We've added 40A AC Ground Bond test capability to HypotULTRA®'s already impressive feature list for manufacturers that aim to adopt best testing practices without sacrificing productivity. Whether you're looking to improve traceability with on-board data storage, increase efficiency with our intuitive touch screen interface and direct barcode scanner connection, or automate with a variety of communication interfaces, HypotULTRA® was designed to take your production line to the next level.



Find the Model that Fits Your Testing Needs



AC Hipot



DC Hipot



40A
Ground Bond



Ground
Continuity



Insulation
Resistance



NEW
2017

	7800*	500 VA*				
	7804	•	•	•	•	•
	7820	•		•		•
	7850	•	•	•	•	•
NEW 2017	7854	500 VA*	•	•	•	•

*Meets 200 mA short circuit requirements

AVAILABLE INTERFACES



USB



RS-232



Ethernet
(Optional)



GPIB
(Optional)

SAFETY & PRODUCTIVITY FEATURES



SmartGFI®
Automatic
operator shock
protection



**Remote Safety
Interlock**
Easily disable
HV output



Data Transfer
Easily import/
export test
files and data
via USB



**Barcode
Capability**
Direct barcode
connection



**Multiple
Languages**
Multi-Language
user interface



**Ground Bond
Voltage Drop**
Monitor
voltage drop
vs resistance



ProVOLT®
Multi-dwell
cycles at
different
voltages for
ACW/DCW/IR



**Internal
Multiplexer**
Available with
optional HV
multiplexer
(4 or 8 ports)



**Modular
Multiplexer**
Compatible
with SC6540
multiplexers



FailCHECK™
Confirms
failure
detection



Prompt & Hold
Provides alerts
& instructions
between tests



Autoware®3
Advanced
Automation
Control
Software



**Advanced
User Security**
Customize ID
& password
protection



Ramp-HI®
Reduce ramp
time during
DC Hipot



Charge-LO®
Confirms
proper DUT
connection



PLC Remote
Basic PLC
relay control



**Negative
DC Hipot**
Reverse
polarity
DC Hipot
(optional)



**On Board Data
Storage**
Save up to
100,000 Test
Results on-board

INPUT SPECIFICATIONS			
Voltage	100 – 120 VAC / 200 – 240 VAC ± 10% Auto Range		
Frequency	50/60 Hz ± 5%		
Fuse	7804/7820/7850:	6.3A, Slow Blow 250 VAC	
	7800/7854:	15A, Fast Blow 250 VAC	
AC WITHSTAND TEST MODE (All Models)			
Output Voltage	Range: Resolution: Accuracy:	0 – 5,000 VAC 1 VAC ± (2% of setting + 5V)	
Output Frequency	50/60 Hz ± 0.1%, User Selection		
Output Waveform	Sine Wave, Crest Factor = 1.3 – 1.5		
Output Regulation	± (1% of output + 5V)		
HI and LO-Limit Total	Total	Range: Resolution: Range: Resolution: Accuracy:	0.000 – 9.999 mA 0.001 mA 10.00 – 30.00 mA (10 – 99.99 mA, Models 7800/7854) 0.01 mA ± (2% of setting + 2 counts) 7804/7820/7850 ± (2% of setting + 6 counts) 7800/7854
	Real	Range: Resolution: Range: Resolution: Accuracy:	0.000 – 9.999 mA 0.001 mA 10.00 – 30.00 mA (10 – 99.99 mA 7800/7854) 0.01 mA ± (3% of setting + 50 µA)
Ramp Up Timer	Range:	0.1 – 999.9 sec	
Ramp Down Timer	Range:	0.0 – 999.9 sec	
Dwell Timer	Range:	0, 0.2 – 999.9 sec (0=Continuous)	
Ground Continuity	Current: DC 0.1A ± 0.01A, fixed		
Current	Max. Ground Resistance: 1.0 Ω ± 0.1 Ω		
Arc Detection	Range:	1 – 9 ranges (9 is most sensitive)	
DC WITHSTAND TEST MODE (Models 7800/7804/7850 & 7854 Only)			
Output Voltage	Range: Resolution: Accuracy:	0 – 6000 VDC 1 V ± (2% of setting + 5 V)	
DC Output Ripple	<4% (6 KV/10 mA at Resistive Load)		
HI and LO-Limit	Range: Resolution: Accuracy:	0.0000 – 0.9999 µA 0.0001 µA ± (2% of setting + 10 counts), Low Range is ON	
	Range: Resolution: Accuracy:	1.000 – 9.999 µA 0.001 µA ± (2% of setting + 10 counts), Low Range is ON	
	Range: Resolution: Accuracy:	10.00 – 99.99 µA 0.01 µA ± (2% of setting + 10 counts), Low Range is ON	
	Range: Resolution: Accuracy:	100.0 – 999.9 µA 0.1 µA ± (2% of setting + 2 counts)	
	Range: Resolution: Accuracy:	1,000 – 20,000 µA range (7804/54) 1,000 – 10,000µA range (7800/50) 1 µA ± (2% of setting + 2 counts)	
Ramp Up Timer	Range:	0.4 - 999.9 sec, Low Range is OFF 0.5 – 999.9 sec, Low Range is ON	
Ramp Down Timer	Range:	0.0, 1.0 – 999.9 sec (0=OFF)	
Dwell Timer	Range:	0, 0.4 – 999.9 sec (0=Continuous) 0, 1.0 – 999.9 sec, Low Range is ON	
Ramp-HI Selectable	Range:	0 – 20 mA selectable	
Charge-LO	Range:	0.0 – 350.0 µA DC or Auto Set	
Discharge Time	< 50 ms for no load, < 100 ms for capacitive load		
Maximum Capacitive Load DC Mode	1µF < 1kV 0.75 µF < 2 kV 0.5 µF < 3 kV	0.0 µF < 4 kV 0.04 µF < 5 kV 0.015 µF < 6 kV	
Arc Detection	Range:	1 – 9 ranges (9 is most sensitive)	
INSULATION RESISTANCE MODE (Models 7800/7804/7850 & 7854 Only)			
Output Voltage, DC	Range: Resolution: Accuracy:	10 – 1,000 VDC 1 VDC ± (2% of setting + 2 counts)	
	Range: Resolution: Accuracy:	1,001 – 6,000 VDC 1 VDC ± (2% of setting + 5 V)	


INSULATION RESISTANCE MODE (Models 7800/7804/7850 & 7854 Only)			
Charging Current HI and LO-Limit	Maximum > 20 mA peak		
	Range:	0.10 MΩ – 99.9 MΩ (HI-Limit: 0=OFF)	
	Resolution:	0.01 MΩ	
	Accuracy:	± (2% of setting + 2 counts)	
	Range:	100.0 MΩ – 999.9 MΩ	
	Resolution:	0.1 MΩ	
	Accuracy:	1,000 – 9,999 ± (5% of setting + 2 counts)	
	Range:	1,000 MΩ – 50,000 MΩ	
	Resolution:	1 MΩ	
	Accuracy:	10,000 – 50,000 ± (15% of setting + 2 counts)	
Ramp Up Timer	Range:	0.1 – 999.9 sec	
Ramp Down Timer	Range:	1.0 – 999.9 sec	
Dwell Timer	Range:	0.5 – 999.9 sec (0=Continuous)	
Delay Timer	Range:	0.5 – 999.9 sec	
Charge-LO	0.000 – 3.500 μA or Auto Set		
CONTINUITY TEST MODE (All Models)			
Output Current, DC	1 A for 0.000 – 1,000 Ω, 0.1 A for 1.01 – 10.00 Ω 0.01 A for 10.01 – 100 Ω, 0.001 A for 101 – 1,000 Ω 0.0001 A for 1001 – 10,000 Ω, 1 A is Max		
Resistance Display Max & Min Max-Lmt	Range:	0.000 – 1,000 Ω	
	Resolution:	0.001 Ω	
	Accuracy:	± (1% of setting + 3 counts)	
	Range:	1.01 – 10.00 Ω	
	Resolution:	0.01 Ω	
	Accuracy:	± (1% of setting + 3 counts)	
	Range:	10.1 – 100.0 Ω	
	Resolution:	0.1 Ω	
	Accuracy:	± (1% of setting + 3 counts)	
	Range:	101 – 1,000 Ω	
	Resolution:	1 Ω	
	Accuracy:	± (1% of setting + 3 counts)	
	Range:	1,001 – 10,000 Ω	
	Resolution:	1 Ω	
	Accuracy:	± (1% of setting + 10 counts)	
Dwell Timer	Range:	0, 0.4 – 999.9 sec (0=Continuous)	
Resistance Offset	Range:	0.000 – 10.00 Ω	
GROUND BOND TEST MODE (Models 7804 & 7854 Only)			
Output Voltage (Open Circuit Voltage)	Range:	3.00 – 8.00 VAC	
	Resolution:	0.01 VAC	
	Accuracy:	± (2% of setting + 3 counts) Open Circuit	
	Output Current	Range:	1.00 – 40.00 A
	Resolution:	0.01 A	
	Accuracy:	± (2% of setting + 2 counts)	
	Maximum Loading	1.00 – 10.00 A, 0 – 600 mΩ 10.01 – 30.00 A, 0 – 200 mΩ 30.01 – 40.00 A, 0 – 150 mΩ	
HI and LO-Limit	Range:	0 – 150 mΩ for 30.01 – 40.00 A 0 – 200 mΩ for 10.01 – 30.00 A 0 – 600 mΩ for 1.00 – 10.01 A	
	Resolution:	1 mΩ	
	Accuracy:	± (2% of setting + 2 counts)	
	Range:	0 – 600 mΩ	
	Resolution:	1 mΩ	
	Accuracy:	± (3% of setting + 3 counts)	
Dwell Timer	Range:	0, 0.5 – 999.9 sec (0=Continuous)	
Milliohm Offset	0 – 200 mΩ		
Voltage Offset	0.0 - 6.0 V		
GENERAL SPECIFICATIONS			
Memory	2,000 steps, 200 steps per test file max 100,000 test results		
Mechanical	Bench or rackmount (2U height) with feet		
Interface	Standard: USB, RS-232 Optional: GPIB (IEEE-488.2), Ethernet or USB Printer		
SmartGFI®	0, 0.4 – 5.0 mA (0=OFF)		
Dimensions (W x H x D)	16.92" x 3.50" x 15.75" (430 x 88.1 x 400mm)		
Weight	7800:	45 lbs (20.4 kg)	
	7804:	41 lbs (18.6 kg)	
	7820:	34 lbs (15.4 kg)	
	7850:	35 lbs (15.9 kg)	
	7854:	46.3 lbs (21 kg)	

OMNIA® II

The Most Advanced Electrical Safety Compliance Analyzer in the Industry



Our OMNIA® II Series is a complete line of multi-function electrical safety compliance analyzers designed to satisfy even the most demanding application requirements. We've included exclusive productivity-enhancing features and the latest in safety technology to make this product line the envy of the industry. With 6 models to choose from, a multi-language menu system and a variety of automation interfaces available, the OMNIA® II is ready for global deployment.



Find the Model that Fits Your Testing Needs



AC Hipot



DC Hipot



Ground Bond



Ground Continuity



Insulation Resistance



Leakage Current



Functional Run



Built-in AC Power



Power Source Recommended



Model	AC Hipot	DC Hipot	Ground Bond	Ground Continuity	Insulation Resistance	Leakage Current	Functional Run	Built-in AC Power	Power Source Recommended
8204	•	•	•	•	•	•	•	•	•
8254	500 VA*	•	•	•	•	•	•	•	•
8206	•	•	•	•	•	•	•	•	•
8256	500 VA*	•	•	•	•	•	•	•	•
8207	•	•	•	•	•	•	•	•	•
8257	500 VA*	•	•	•	•	•	•	•	•

*Meets 200 mA short circuit requirements

AVAILABLE INTERFACES



USB



RS-232



Ethernet
(Optional)



GPIB
(Optional)

SAFETY & PRODUCTIVITY FEATURES



SmartGFI®
Automatic operator shock protection



Remote Safety Interlock
Easily disable HV output



Prompt & Hold
Provides alerts & instructions between tests



Multiple Languages
Multi-Language user interface



Active Link®
Continuous power during test steps



My Menu
Customize your own shortcut menu



DualCHEK®
Simultaneous Hipot and Ground Bond



Internal Multiplexer
Available with optional HV multiplexer (4 or 8 ports)



Modular Multiplexer
Compatible with SC6540 multiplexers



PLC Remote
Basic PLC relay control



FailCHEK™
Confirms failure detection



Cal-Alert®
Tracks and alerts for calibration



Ramp-HI®
Reduce ramp time during DC Hipot



Charge-LO®
Confirms proper DUT connection



Arc Detection
High frequency filter for corona detection



Autaware®3
Advanced Automation Control Software



Accredited Cal
Accredited calibration options available



Ground Bond Voltage Drop
Monitor voltage drop vs resistance

INPUT SPECIFICATIONS			
Voltage	115/230 V Auto Range, ± 15 % Variation		
Frequency	50/60 Hz ± 5%		
Fuse	115 VAC, 230 VAC – 10 A Slow Blow 250 VAC		
DIELECTRIC WITHSTAND TEST MODE			
Output Rating	5 kV @ 50 mAAC 5 kV @ 100 mAAC (Models 825X) 6 kV @ 20 mADC		
Voltage Setting	Resolution: Accuracy:	1 V ± (2% of setting + 5 volts)	
HI and LO-Limit	AC Total	Range: Resolution:	0.000 – 9.999 mA 0.001 mA
		Range: Resolution:	10.00 – 50.00 mA (100.00 mA, models 825X) 0.01 mA
		Accuracy:	± (2% of setting + 2 counts)
	AC Real	Range: Resolution:	0.000 – 9.999 mA 0.001 mA
		Range: Resolution:	10.00 – 50.00 mA (100.00 mA, models 825X) 0.01 mA
		Accuracy:	± (3% of setting + 50 µA)
	DC	Range: Resolution:	0 – 999.9 µA 0.1 µA
Range: Resolution:		1,000 – 20,000 µA 1 µA	
Accuracy:		± (2% of setting + 2 counts)	
Arc Detection	Range:	1 – 9 (9 is most sensitive)	
Ground Continuity	Current: DC 0.1 A ± 0.01 A, fixed Max. Ground Resistance: 1 Ω ± 0.1 Ω, fixed		
Ground Fault Interrupt	GFI Trip Current: 0.4 mA – 5.0 mA (AC or DC) HV Shut Down Speed: < 1 ms		
DC Output Ripple	≤ 4% Ripple rms at 5 kVDC at 20 mA Resistive Load		
Discharge Time	≤ 50 ms No Load, < 100 ms for Capacitive Load		
Max Capacitive Load, DC Mode	1 µF < 1 kV 0.08 µF < 4 kV 0.75 µF < 2 kV 0.04 µF < 6 kV 0.5 µF < 3 kV		
AC Output Waveform	Sine Wave, Crest Factor = 1.3 – 1.5		
Output Frequency	Range:	60 or 50 Hz, User Selection (400/800 Hz optional)	
Output Regulation	± (1% of output + 5 V) from no load to full load and over input voltage range		
Dwell Timer	Range: Range:	AC 0.4 – 999.9 sec (0=Continuous) DC 0.3 – 999.9 sec (0=Continuous)	
Ramp Timer	Ramp-up: Ramp-Down:	AC 0.1 – 999.9 sec, DC 0.4 – 999.9 sec AC 0.0 – 999.9 sec, DC 0.0 , 1.0 – 999.9 sec (0=Continuous)	
INSULATION RESISTANCE TEST MODE			
Voltage Setting	Range:	30 – 1000 VDC	
HI and LO-Limit	Range: Resolution:	0.05 MΩ – 99.99 MΩ 0.01 MΩ	
	Range: Resolution:	100.0 MΩ – 999.9 MΩ 0.1 MΩ	
	Range: Resolution:	1,000 MΩ – 50,000 MΩ 1 MΩ (HI-Limit: 0=OFF)	
	Ramp Timer	Ramp-up: Ramp-Down:	0.1 – 999.9 sec 0.0, 1.0 – 999.9 sec (0=Continuous)
Delay Timer	Range:	0.5 – 999.9 sec (0=Continuous)	

GROUND BOND TEST MODE		
Output Voltage (Open Circuit Limit)	Range: 3.00 – 8.00 VAC	
Output Frequency	Range: 60 or 50 Hz, User Selectable	
Output Current	Range: 1.00 – 40.00 A Resolution: 0.01 A Accuracy: $\pm (2\% \text{ of setting} + 0.02 \text{ A})$	
Maximum Loading	1.00 – 10.00 A, 0 – 600 m Ω 10.01 – 30.00 A, 0 – 200 m Ω 30.01 – 40.00 A, 0 – 150 m Ω	
HI and LO-Limit	Range: 0 – 150 m Ω for 30.01 – 40.00 A 0 – 200 m Ω for 10.01 – 30.00 A 0 – 600 m Ω for 1.00 – 10.00 A Resolution: 1 m Ω Accuracy: $\pm (2\% \text{ of reading} + 2 \text{ m}\Omega)$	
	Range: 0 – 600 m Ω for 1.00 – 5.99 A Resolution: 1 m Ω Accuracy: $\pm (3\% \text{ of reading} + 3 \text{ m}\Omega)$	
Dwell Timer	Range: 0.5 – 999.9 sec (0=Continuous)	
Milliohm Offset	Range: 0 – 200 m Ω	
CONTINUITY TEST MODE		
Output Current	DC 0.01 A ± 0.00001 A	
Resistance Display	Range: 0.00 – 10000 Ω	
HI and LO-Limit	Range: 1: 0.00 – 10.00 Ω Resolution: 0.01 Ω	
	Range 2: 10.1 – 100.0 Ω Resolution: 0.1 Ω	
	Range 3: 101 – 1,000 Ω Resolution: 1 Ω Accuracy: $\pm (1\% \text{ of reading} + 3 \text{ counts})$	
	Range 4: 1,001 – 10,000 Ω Resolution: 1 Ω Accuracy: $\pm (1\% \text{ of reading} + 10 \text{ counts})$ (Max Limit: 0=OFF)	
Dwell Timer	Range: 0.0, 0.3 – 999.9 sec (0=Continuous)	
Milliohm Offset	Range: 0.00 – 10.00 Ω	
RUN TEST MODE (Models 82X6 & 82X7 only)		
DUT Power	Voltage: 0 – 277 VAC single phase unbalanced	
	Current: 16 AAC max continuous	
	Range: 0.0 – 277.0 VAC Full Scale Resolution: 0.1 V Accuracy: $\pm (1.5\% \text{ of reading} + 0.2 \text{ V})$, 30.0 – 277.0 VAC Short Circuit Protection: 23 AAC, Response Time < 3 sec	
Delay Time Setting	Range: 0.2 – 999.9 seconds	
Dwell Time Setting	Range: 0.1 – 999.9 seconds (0=Continuous)	

RUN TEST MODE CONTINUED (Models 82X6 & 82X7 only)			
Trip Point Settings & Metering	Voltage		
	Volt-Hi Volt-LO	Range: Resolution: Accuracy:	30.0 – 277.0 VAC 0.1 V ± (1.5% of setting + 0.2 V), 30.0–277 VAC
	Current		
	Amp-HI Amp-LO	Range: Resolution: Accuracy:	0.0 – 16.00 AAC 0.01 A ± (2.0% of setting + 2 counts)
	Watts		
	Power-HI Power-LO	Range: Resolution: Accuracy:	0 – 4,500 W 1 W ± (5.0% of setting + 3 counts)
	Power Factor		
	PF-HI PF-LO	Range: Resolution: Accuracy:	0.000 – 1.000 0.001 ± (8% of setting + 2 counts)
	Leakage Current		
	Leak-HI Leak-LO	Range: Resolution: Accuracy:	0.00 – 10.00 mA (0=OFF) 0.01 mA ± (2% of setting + 2 counts)
Timer Display	Range: Resolution: Accuracy:	0.0 – 999.9 seconds 0.1 second ± (0.1% of reading + 0.05 seconds)	
LEAKAGE CURRENT TEST MODE (Models 82X6 & 82X7 only)			
DUT Power	Voltage: Current:	0 – 277 VAC 16 AAC max continuous	
	Voltage Display	Range: Resolution: Accuracy:	0.0 – 277.0 VAC Full Scale 0.1 V ± (1.5% of reading +0.2 V), 30.0 – 277.0 VAC
	Short Circuit Protection:	23 AAC, Response Time < 3 s	
Reverse Power Switch	Reverse polarity switch setting select ON/OFF/AUTO ON: Reverse power OFF: Normal AUTO: Automatic Reverse Polarity		
Neutral Switch	ON/OFF selection for single fault condition		
Ground Switch	ON/OFF selection for Class I single fault condition		
Probe Setting	Surface to Surface (PH – PL) Surface to Line (PH – L) Ground to Line (G – L)		
Touch Current High Limit (rms)	Range: Resolution:	0.0 µA ~ 999.9 µA 1000 µA ~ 10.00 mA 0.1 µA / 1 µA / 0.01 mA	

LEAKAGE CURRENT TEST MODE CONTINUED (Models 82X6 & 82X7 only)		
Touch Current Display (rms)	Range 1:	0.0 µA ~ 32.0 µA, frequency DC, 15 Hz – 1 MHz
	Range 2:	28.0 µA ~ 130.0 µA, frequency DC, 15 Hz – 1 MHz
	Range 3:	120.0 µA ~ 550.0 µA, frequency DC, 15 Hz – 1 MHz
	Resolution for Ranges 1, 2, 3:	0.1 µA
	Accuracy for Ranges 1, 2, 3:	DC: 15 Hz < f <100 KHz: ± (2% of reading + 3 counts) 100 KHz < f < 1 MHz: ± 5% of reading (10.0 µA – 999.9 µA)
	Range 4:	400 µA ~ 2100 µA, frequency DC, 15 Hz – 1 MHz
	Range 5:	800 µA ~ 8500 µA, frequency DC, 15 Hz – 1 MHz
	Resolution for Ranges 4 & 5:	1 µA
	Accuracy for Ranges 4 & 5:	DC: 15 Hz < f <100 KHz: ± (2% of reading + 3 counts) 100 KHz < f < 1 MHz: ± 5% of reading (10 µA – 8500 µA)
	Range 6:	8.00 mA ~ 10.00 mA, frequency DC 15 Hz – 100 kHz
	Resolution:	0.01 mA
	Accuracy:	DC: 15 Hz < f < 100 KHz: ± 5% of reading (0.01 mA -10.00 mA)
Touch Current Display (Peak)	Range 1:	0.0 µA ~ 32.0 µA, frequency DC – 1 MHz
	Range 2:	28.0 µA ~ 130.0 µA, frequency DC – 1 MHz
	Range 3:	120.0 µA ~ 550.0 µA, frequency DC – 1 MHz
	Resolution for Ranges 1, 2, 3:	0.1 µA
	Accuracy for Ranges 1, 2, 3:	DC: ± (2% of reading + 2 µA) 15 Hz < f < 1 MHz : ± 10% of reading + 2 µA
	Range 4:	400 µA ~ 2100 µA, frequency DC – 1 MHz
	Range 5:	1800 A ~ 8500 µA, frequency DC – 1 MHz
	Resolution for Ranges 4 & 5:	1 µA
	Accuracy for Ranges 4 & 5:	DC: ± (2% of reading + 2 µA) 15 Hz < f < 1 MHz: ±(10% of reading + 2 µA)
	Range 6:	8.0 mA ~10.00 mA, frequency DC – 100 KHz
	Resolution:	0.01 mA
	Accuracy:	DC: ± (2% of reading + 3 counts) 15 Hz < f < 100 KHz: ± (10% of reading + 2 counts)
MD Circuit Module	MD1: UL544NP, UL484 , UL923, UL471, UL867, UL697 MD2: UL544P MD3: IEC 60601-1 MD4: UL1563 MD5: IEC60990 Fig4 U2, IEC 60950-1, IEC60335-1, IEC60598-1, IEC60065, IEC61010 MD6: IEC60990 Fig5 U3, IEC60598-1 MD7: IEC60950, IEC61010-1 FigA.2 (2K ohm) for Run function MD8: IEC60990/60950 Fig4 U1	
External MD	Basic measuring element 1 kΩ	
Scope Output Interface	BNC type connector on rear panel for Oscilloscope connection	

AC POWER SOURCE (82X7 only)			GENERAL SPECIFICATIONS		
Output	Power:	630 VA and 500 W Maximum		PLC Remote Control	Input: Test, Reset, Interlock, Recall File 1 through 3 Output: Pass, Fail, Test-in-Process
	Voltage:	0 – 150.0 V / 0 – 277.0 V		Safety	Built-in SmartGFI circuit
	Current:	4.20 A maximum for 0 – 150 V range 2.10 A maximum 0 – 277 V range		Memory	10,000 Steps
	Distortion:	≤ 1% at 45- 500 Hz and output voltage within the 80 ~ 140 VAC at Low Range or the 160 ~ 277 VAC at High Range (Resistive Load)		Interface	Standard: USB/RS-232 Optional: Ethernet or GPIB
	Regulation:	≤ 0.5% + 5 V (resistive load), from no load to full load and Low Line to High Line (combined regulation)		Security	Advanced security system with access levels and username/password requirements
	Crest Factor:	> 3		Dimensions (W x H x D)	16.93" x 5.24" x 19.69" (430 x 133 x 500 mm)
	Test Timing:	< 350 ms at start and between		Weight	8204: 82 lbs (37 kg) 8254: 92 lbs (42 kg) 8206/8207: 83 lbs (38 kg) 8256/8257: 103 lbs (47 kg)
	Limit:	Steps when internal AC source is ON			
Settings	Voltage	Low Range:	0.0 – 150.0 V		
		High Range:	0.0 – 277.0 V		
		Resolution:	0.1 V		
		Accuracy:	± (1.5% of setting + 2 counts)		
	Frequency	Range:	45.0 Hz – 99.9 Hz		
		Resolution:	0.1 Hz		
		Accuracy:	± 0.1% of setting		
		Range:	100 Hz – 500 Hz		
A-HI-Limit	Resolution:	1 Hz			
	Accuracy:	± 0.1% of setting			
Measurement	Voltage	Range:	4.20 A / 2.10 A		
		Resolution:	0.01 A		
		Accuracy:	± (2% of reading + 2 counts)		
		Range:	0.0 – 277.0 V		
		Resolution:	0.1 V		
	Current	Accuracy:	± (1.5% of reading + 2 counts)		
		Range:	0.00 – 16.00 A		
		Resolution:	0.01 A		
Power	Accuracy:	± (2% of reading + 2 counts)			
	Power:	0 – 4500			
	Resolution:	1			
Power Factor	Accuracy:	± (5% of reading + 3 counts) for PF > 0.100			
	Power Factor:	0.000 – 1.000			
	Resolution:	0.001			
Frequency	Accuracy:	± (8% of reading + 5 counts)			
	Frequency:	45 – 500 Hz			
	Resolution:	0.1 Hz			
	Accuracy:	± 0.1 Hz			

Why We Use Counts

Associated Research publishes some specifications using “counts” which allows us to provide a better indication of the instrument’s capabilities across measurement ranges. A count refers to the lowest resolution of the display for a given measurement range. For example, if the resolution for voltage is 1V then 2 counts = 2 V.

Specifications subject to change without notice.

Why We Use Counts

Associated Research publishes some specifications using “counts” which allows us to provide a better indication of the instrument's capabilities across measurement ranges. A count refers to the lowest resolution of the display for a given measurement range. For example, if the resolution for voltage is 1V then 2 counts = 2 V.

Specifications subject to change without notice.

HYAMP®

The Industry Leading Production
Line Ground Bond Instrument



Our new HYAMP® Series provides manufacturers with data-driven results and greater test flexibility required in today's complex test environment. Quickly collect test data and test settings from the convenient front panel USB port onto a standard USB flash drive. Use the front panel barcode connection to associate products with preprogrammed test files. Test with greater flexibility by performing either AC Ground Bond or DC Ground Bond at a maximum of 40 A of current. The new HYAMP® features a drastically reduced weight and footprint making it the ideal lightweight Ground Bond solution for laboratory and production line testing applications. Easily interconnect with the Hypot® Series to form a complete safety compliance system.



Find the Model that Fits Your Testing Needs



Ground Bond

NEW
2017

3240

AC/DC

AVAILABLE INTERFACES



USB

SAFETY & PRODUCTIVITY FEATURES



PLC Remote
Basic PLC
relay control



**Remote Safety
Interlock**
Easily disable
HV output



Data Transfer
Easily import/
export test
files and data
via USB



**Barcode
Capability**
Direct barcode
connection



**Multiple
Languages**
Multi-Language
user interface



**Ground Bond
Voltage Drop**
Monitor
voltage drop
vs resistance



FailCHECK™
Confirms
failure
detection



Prompt & Hold
Provides alerts
& instructions
between tests



**Advanced
User Security**
Customize ID
& password
protection



**Accredited
Cal**
Accredited
calibration
options
available



**4-Wire
Measurement**
More accurate
milliohm
measurement



Interconnection
Interconnect with
Hypot® to form
a complete test
system



**On Board Data
Storage**
Save up to
1,500 Test
Results on-board

INPUT SPECIFICATIONS		
Voltage	100 – 120 VAC / 200 – 240 VAC ± 10% Auto Range	
Frequency	50/60Hz ± 5%	
Fuse	10 A, Slow Blow 250 VAC	
GROUND BOND TEST MODE		
Output Voltage (Open Circuit Voltage)	Range: Resolution: Accuracy:	3.00 – 8.00 VAC/DC 0.01 VAC/DC ± (3% of setting + 3 counts)
Output Frequency	50 or 60 Hz, User Selectable/DC	
Output Current	Range: Resolution: Accuracy:	0 – 150 mΩ for 30.01 – 40.00 A 0 – 200 mΩ for 10.01 – 30.00 A 0 – 600 mΩ for 1.00 – 10.01 A 0.1 A ± (3% of setting + 3 counts)
Maximum Loading	Range: Resolution: Accuracy:	1.00 – 10.00 A, 0 – 600 mΩ 10.01 – 30.00 A, 0 – 200 mΩ 30.01 – 40.00 A, 0 – 150 mΩ 1 mΩ ± (2% of setting + 2 counts)
HI and LO-Limit Resistance	Range: Resolution: Accuracy:	0 – 150 mΩ for 30.01 – 40.00 A 0 – 200 mΩ for 10.01 – 30.00 A 0 – 600 mΩ for 1.00 – 10.01 A 1 mΩ ± (2% of setting + 2 counts)
HI and LO-Limit Voltage	Range: Resolution: Accuracy:	0.00 – 6.00 V 0.01 ± (2% of settings + 2 counts)
Dwell Time Setting	Range:	0, 0.5 – 999.9 sec (0=Continuous)
Ω Offset Capability	Range: Resolution: Accuracy:	0 – 100 mΩ 1 mΩ ± (2% of setting + 2 counts)
V Offset Capability	Range: Resolution: Accuracy:	0.00 – 4.00 V 0.01 V ± (2% of setting + 2 counts)
Current Display	Range: Resolution: Accuracy:	0.00 – 40.00 AAC/DC 0.01 AC/DC ± (3% of reading + 1 count)
Voltage Display	Range: Resolution: Accuracy:	0.00 – 8.00 VAC/DC 0.01 AC/DC ± (2% of reading + 2 counts)
Ohmmeter Display	Range: Resolution: Accuracy:	0 – 600 mΩ for 1.00 – 5.99 A 1 mΩ ± (3% of reading + 3 counts)
	Range: Resolution: Accuracy:	0 – 600 mΩ for 6 – 40 A 1 mΩ ± (2% of reading + 2 counts)

GENERAL SPECIFICATIONS	
Remote Control and Signal I/O	The following input and output signals are provided through two 9 pin D type connectors: Inputs: Test, Reset, Hardware Interlock, File Recall Outputs: Pass, Fail, Test-in-Process, Reset-Out, Start-Out Hardware Interlock (safety)
Memories	50 steps 1500 test results
Interface	USB standard
Language	English, Traditional Chinese, Simplified Chinese, Turkish, Portuguese, Spanish, German, French
Security	Multiple user setups with ID and password
Dimensions (W x H x D)	8.5" x 3.5" x 11.9" (215 x 88.1 x 300 mm)
Weight	11 lbs (5 kg)

Why We Use Counts

Associated Research publishes some specifications using "counts" which allows us to provide a better indication of the instrument's capabilities across measurement ranges. A count refers to the lowest resolution of the display for a given measurement range. For example, if the resolution for voltage is 1V then 2 counts = 2 V.

Specifications subject to change without notice.

HypotMAX®

The Safest and Most Reliable Automated High Voltage Hipot Instrument Available



Our HypotMAX® Series is a complete line of automated Hipot instruments designed to meet the demanding requirements of high voltage applications. We've included our patented SmartGFI® feature for maximum operator safety as well as a variety of advanced features to increase productivity on the production line and in the lab. Set up and run tests with confidence from our intuitive user interface or automate with a PC.



AVAILABLE INTERFACES



USB



RS-232



GPIB
(Optional)

SAFETY & PRODUCTIVITY FEATURES



PLC Remote
Basic PLC relay control



SmartGFI®
Automatic operator shock protection



Remote Safety Interlock
Easily disable HV output



Arc Detection
High frequency filter for corona detection



Ramp-HI®
Reduce ramp time during DC Hipot



Charge-LO®
Confirms proper DUT connection



Accredited Cal
Accredited calibration options available



Autaware®
Use with automation software control

Find the Model that Fits Your Testing Needs



AC Hipot



DC Hipot

7705	•
7710	•
7715	•
7720	•

INPUT SPECIFICATIONS			
Voltage	115/130 VAC ± 10%, Single Phase, User Selection		
Frequency	50/60 Hz ± 5%		
Fuse	6.3 A, 250 V Slow Blow		
DIELECTRIC WITHSTAND TEST MODE			
Output Rating	7705: 7710: 7715: 7720:	10 kV @ 20 mAAC 12 kV @ 10 mADC 20 kV @ 10 mAAC 20 kV @ 5 mADC	
HI-Limit and LO-Limit	7705	Range 1: Resolution: Range 2: Resolution:	0.0 – 9.999 mA 0.001 mA 10.00 – 20.00 mA 0.01 mA
	7710	Range 1: Resolution: Range 2: Resolution:	0.00 – 999.9 µA 0.1 uA 1,000 – 9,999 µA 1 µA
	7715	Range: Resolution:	0.00 – 9.999 mA 0.001 mA
	7720	Range 1: Resolution: Range 2: Resolution:	0.0 – 999.9 µA 0.1 µA 1,000 – 5,000 µA 1 µA/step
	77XX	Accuracy:	± (2% of setting + 2 counts)
DC Ramp HI	7710	13 mA peak maximum, 10 mADC, ON/OFF selectable	
	7720	6.75 mA peak maximum, 5 mADC, ON/OFF selectable	
DC Charge LO	7710/7720	Range:	0.0 – 350 µADC or auto set
Arc Detection	7705	1 – 9 at output voltage < 7.00 kV 1 – 8 at output voltage ≥ 7.00 kV	
	7710/7720	1 – 9	
	7715	1 – 9 at output voltage < 15.00 kV 1 – 7 at output voltage ≥ 15.00 kV	
Voltage Display	7705	Range: Accuracy:	0.00 – 10.00 kV Full scale ± (2% of reading + 20 V)
	7710	Range: Accuracy:	0.00 – 12.00 kV Full scale ± (2% of reading + 20 V)
	7715/7720	Range: Accuracy:	0.00 – 20.00 kV Full scale ± (2% of reading + 20 V)
Current Display	7705	Auto Range Range 1: Range 2:	0.000 – 3.500 mA 3.00 – 20.00 mA
	7710	Auto Range Range 1: Range 2: Range 3:	0.0 – 350.0 µA 300 – 3500 µA 3,000 – 9,999 µA
	7715	Auto Range Range 1: Range 2:	0.000 – 3.500 mA 3.00 – 10.00 mA
	7720	Auto Range Range 1: Range 2:	0.0 – 350.0 µA 300 – 5,000 µA
DC Output Ripple	7710	< 5% Ripple at 12 kV @ 9,999 µA, Resistive Load	
	7720	< 5% Ripple at 20 kV @ 4,999 µA, Resistive Load	
AC Output Waveform	Sine Wave, Crest Factor = 1.3 – 1.5		
Output Frequency	Range:	50/60 Hz, User Selection ± (1% of output + 5 V) from Regulation No load to full load	
Output Regulation	± (1% of output + 10 V) from no load to full load		
Discharge Timer	7710	No load < 400 ms	
	7720	No load < 500 ms	
Dwell Timer		Range: AC Range: DC Range:	0, 0.3 – 999.9 sec (0=Continuous) 0, 0.3 – 999.9 sec or min (0=Continuous) 0, 0.4 – 999.9 sec or min (0=Continuous)
Ramp Timer	7705/7715	Range:	0.3 – 999.9 sec
	7710/7720	Range:	0.4 – 999.9 sec
Ground Continuity	Max. Ground Resistance 1 Ω ± 0.1 Ω, fixed		

DIELECTRIC WITHSTAND TEST MODE

Ground Fault Interrupt	HV Shut Down Speed < 1 ms GFI Trip Current 1 mA max
------------------------	--

GENERAL SPECIFICATIONS

Memory	50 memories w/ 8 steps per memory		
Mechanical	Tilt-up front feet		
Interface	Standard: USB, RS-232 Optional: GPIB		
Dimensions (W x H x D)	16.93" x 5.24" x 15.75" (430 x 133 x 400 mm)		
Weight	7705/7710:	61.65 lbs (28 kg)	
	7710/7720:	48.9 lbs (22 kg)	

Why We Use Counts

Associated Research publishes some specifications using “counts” which allows us to provide a better indication of the instrument's capabilities across measurement ranges. A count refers to the lowest resolution of the display for a given measurement range. For example, if the resolution for voltage is 1V then 2 counts = 2 V.


Specifications subject to change without notice.

SC6540

The Patented Multiplexer that Revolutionized Production Line and Laboratory Electrical Safety Compliance Testing



Our patented SC6540 multiplexer pioneered the largest productivity improvement in the electrical safety compliance industry in years. With up to 16 independent high voltage or high current channels in a convenient 2U design, the SC6540 can be customized in 10 different configurations for multi-point Hipot, Ground Bond, Insulation Resistance, and Leakage Current testing. Configure the SC6540 according to your needs, and interface with your OMNIA® II, HypotULTRA® or LINECHECK® II instrument to improve production line throughput or expand lab testing capability. Operate from the front panel of your AR instrument or utilize a variety of automation interfaces for direct PC control.



Find the Model that Fits Your Testing Needs



High Voltage



High Current



8 Channel



16 Channel

HN	•		•	
HH	•			•
HG	•	•		•
GN		•	•	
GG		•		•

Available in both main and secondary configurations

AVAILABLE INTERFACES



USB



RS-232



Ethernet
(Optional)



GPIB
(Optional)

PRODUCTIVITY ENHANCING FEATURES



BatchTEST®
Simultaneous
DUT testing
with AW2



Interconnection
Interconnect
with the
HypotULTRA®,
OMNIA® II or
LINECHECK® II to
form a complete
test system



Autoware®3
Advanced
Automation
Control
Software

FOR USE WITH THE FOLLOWING TESTS



AC Hipot



DC Hipot



Ground Bond



Ground
Continuity



Insulation
Resistance



Leakage
Current

MODULAR MULTIPLEXER SPECIFICATIONS

Input (Main only)	115 VAC ($\pm 10\%$), 50/60 Hz, single phase 230 VAC ($\pm 10\%$), 50/60 Hz, single phase User selectable
Fuse (Main only)	250 V/2 A/fast-blow
PC Control (Main only)	Standard: USB, RS-232 Optional: Ethernet, GPIB
Multiplexer Control	Main: One Multiplexer bus output controls, up to 4 additional secondaries Secondary: One output and one input
Maximum HV Rating	5 kV AC and DC
Maximum HC Rating	40 A
Number of Possible Channels	8 or 16
HV Output	100' reel HV cable rated for up to 30 kV Terminations with 8 HV connectors
GND Output	20 terminals provided, to accept 10/12 AWG Terminations hook-up wire (user supplied wire)
Temperature	32° – 104° F (0° – 40° C)
Humidity	0 – 80%
Altitude	6,560 ft. (2,000 m)
Mechanical	2U with tilt-up front feet
Dimensions (W x H x D)	17" x 4.07" x 12.96" (432 x 103 x 329 mm)
Weight	Main: 20.05 lbs. max. (9.09 kg) (with 2 high voltage modules) Secondary: 15.45 lbs. max. (7.01 kg) (with 2 high voltage modules)

CONFIGURATIONS

The modular design can be customize to fit your application. In addition to main or secondary control, the SC6540 can be set up in the following configurations: 8 or 16 high voltage channels, 8 or 16 high current channels, and 8 high voltage channels and/or 8 high current channels. Refer to the images for details.

The different configurations (shown below) are indicated by the following alpha designators

M – Main Multiplexer
H – 8 High Voltage Channels
HH – 16 High Voltage Channels
G – 8 Ground Bond Channels
GG – 16 Ground Bond Channels
N – Empty Module
S – Secondary



MODEL SC6540 HNM*

8 Channel High Voltage Multiplexer



MODEL SC6540 HHM*

16 Channel High Voltage Multiplexer



MODEL SC6540 HGM*

8 Channel High Voltage Multiplexer
8 Channel High Current Multiplexer



MODEL SC6540 GNM*

8 Channel High Current Multiplexer



MODEL SC6540 GGM*

16 Channel High Current Multiplexer


*Also available in secondary configuration

LINECHEK® II

The Fully Automated Leakage Current Instrument that Changed the Industry



Our LINECHEK® II model 620L provides 7 measuring devices (MD's) compliant with international certification bodies as well as a convenient switching network to simulate all 8 required fault conditions, everything you need for full Leakage Current compliance. Utilize the intuitive user interface or control via a PC for more advanced automated applications that require data storage and analysis. The 620L handles up to 40 A of continuous current and can be interfaced to an SC6540 modular multiplexer for multi-point testing. Interconnect the 620L to an OMNIA® II instrument to form a complete electrical safety compliance testing system.



AVAILABLE INTERFACES



USB



RS-232



Ethernet
(Optional)



GPIB
(Optional)

SAFETY & PRODUCTIVITY FEATURES



Prompt & Hold
Provides alerts & instructions between tests



Remote Safety Interlock
Easily disable HV output



Active Link®
Continuous power during test steps



PLC Remote
Basic PLC relay control



Modular Multiplexer
Compatible with SC6540 multiplexers



Interconnection
Interconnect with OMNIA® II or HypotULTRA® to form a complete test system



Cal-Alert®
Tracks and alerts for calibration

Find the Model that Fits Your Testing Needs



Leakage Current



Functional Run



Power Source Recommended

620L

•

•

•

INPUT SPECIFICATIONS		
Voltage	115/230 VAC ± 10%, User Selection	
Frequency	50/60 Hz ± 5%	
Fuse	2 A Slow Blow 250 VAC	
LINE CONDITIONS		
Reverse Power Switch	Switch for power polarity reversal	
Neutral Switch	Neutral switch on/off selection for single fault	
Ground Switch	Ground switch on/off selection for class I single fault	
PROBE SETTINGS		
Surface to Surface	(PH – PL)	
Surface to Line	(PH – L)	
Ground to Line	(G – L)	
LEAKAGE LIMIT SETTINGS		
Touch Current High/Low Limit (rms)	Range: Resolution:	0.0 µA – 999.9 µA / 1,000 µA – 9,999 µA / 10.00 mA – 20.00 mA 0.1 µA / 1 µA / 0.01 mA
Touch Current High/Low Limit (Peak)	Range: Resolution:	0.0 µA -999.9 µA / 1,000 uA – 9,999 µA / 10.00 mA – 30.00 mA 0.1 µA / 1 µA / 0.01 mA
DISPLAY		
Touch Current Display (rms)	Range: Resolution: Accuracy:	0.0 µA – 550 µA, frequency DC, 15 Hz – 1 MHz 0.1 µA DC: 15 Hz ≤ f ≤ 100 kHz: ± (2% of reading + 3 counts) 100 kHz ≤ f ≤ 1 MHz: ± 5% of reading (10.0 µA – 999.9 µA)
	Range: Resolution: Accuracy:	400 µA – 8,500 µA, frequency DC, 15 Hz – 1 MHz 1 µA DC: 15 Hz ≤ f ≤ 100 kHz: ± (2% of reading + 3 counts) 100 kHz ≤ f ≤ 1 MHz: ± 5% of reading, (10.0 µA – 8,500 µA)
	Range: Resolution: Accuracy:	8.00 mA – 20.00 mA, frequency DC, 15 Hz – 100 KHz 0.01 mA DC: 15 Hz ≤ f ≤ 100 MHz: ± 5% of reading (0.01 mA – 20.00 mA)
Touch Current Display (peak)	Range: Resolution: Accuracy:	0.0 µA – 550 µA, frequency DC – 1 MHz 0.1 µA ± (2% of reading + 2 µA) 15 Hz ≤ f ≤ 1 MHz, ± 10% of reading + 2 µA
	Range: Resolution: Accuracy:	400 µA – 8,500 µA, frequency DC – 1 MHz 1 µA ± (2% of reading + 2 µA) 15 Hz ≤ f ≤ 1 MHz, ± 10% of reading + 2 µA
	Range: Resolution: Accuracy:	8.00 mA – 30.00 mA, frequency DC – 100 kHz 0.01 mA ± (2% of reading + 3 counts) 15 Hz ≤ f ≤ 100 kHz, ± 10% of reading + 2 counts
MEASURING DEVICE MODULE		
MD1	UL544NP, UL484 , UL923, UL471, UL867, UL697	
MD2	UL544P	
MD3	IEC 60601-1	
MD4	UL1563	
MD5	IEC60990 Fig4 U2, IEC60950-1, IEC60335-1, IEC60598-1,IEC60065, IEC61010	
MD6	IEC60990 Fig5 U3, IEC60598-1	
MD7	IEC60950, IEC61010-1 FigA.2 (2 kohm) for Run function	
External MD	Basic measuring element 1 kohm	
MD Voltage Limit	70 VDC	

DUT POWER		
AC Voltage	0.0 – 277.0 V	
AC Current	40 A max continuous	
AC Voltage High/Low Limit	Range: Resolution:	0.0 – 277.0 V 0.1 V/step
AC Voltage Display	Range: Resolution: Accuracy:	0.0 – 277.0 V 0.1 V/step ± (1.5% of reading + 2 counts), 30.0 – 277.0 V
Delay Time Setting	Range: Resolution:	0.5 – 999.9 sec 0.1 sec
Dwell Time Setting	Range: Resolution: Accuracy:	0, 0.5 – 999.9 sec (0=Continuous) 0.1 sec ± (0.1% of reading + 0.05 seconds)
Failure Protection	On Start-Up – Neutral Voltage Check (Neutral – V) Over current and ground current check (Line – OC)	
GENERAL SPECIFICATIONS		
Memory	50 Memories, 30 steps per each memory File locations can link 900 steps max	
Mechanical	Bench or rackmount with tilt-up feet	
Interface	Standard: USB, RS-232 Optional: Ethernet, GPIB	
Dimensions (W x H x D)	16.93" x 5.24" x 11.81" (430 x 133 x 300 mm)	
Weight	26.45 lbs (12 kg)	

Why We Use Counts

Associated Research publishes some specifications using “counts” which allows us to provide a better indication of the instrument’s capabilities across measurement ranges. A count refers to the lowest resolution of the display for a given measurement range. For example, if the resolution for voltage is 1V then 2 counts = 2 V.

Specifications subject to change without notice.

MedTEST

A Complete Electrical Safety Testing System that Satisfies the Most Demanding Medical Compliance Requirements



Our MedTEST system can be designed to provide complete test solution for medical device manufacturers in need of conforming to IEC 60601-1 3rd Edition Standard. Customize your MedTEST system to satisfy your individual testing requirements including Hipot, Ground Bond, Insulation Resistance, Functional Run and leakage current testing for all B, BF and CF type applied parts including Mains on Applied Parts (MOAP) tests. Up to 40 A of continuous DUT current combined with our Active Link® technology reduces overall test time and integration with our SC6540 modular multiplexer allows for multi-point sequential testing without the need to change test leads. Get the most from your test system by utilizing our Autoware®3 software for maximum productivity-enhancing benefits.



AVAILABLE INTERFACES



USB



RS-232



Ethernet
(Optional)



GPIB
(Optional)

SAFETY & PRODUCTIVITY FEATURES



SmartGFI®
Automatic operator shock protection



Remote Safety Interlock
Easily disable HV output



Prompt & Hold
Provides alerts & instructions between tests



Multiple Languages
Multi-Language user interface



Active Link®
Continuous power during test steps



My Menu
Customize your own shortcut menu



DualCHEK®
Simultaneous Hipot and Ground Bond



Internal Multiplexer
Available with optional HV multiplexer



Modular Multiplexer
Compatible with SC6540 multiplexers



FailCHEK™
Confirms failure detection



Cal-Alert®
Tracks and alerts for calibration



Ramp-HI®
Reduce ramp time during DC Hipot



Charge-LO®
Confirms proper DUT connection



Autoware®3
Advanced Automation Control Software



Accredited Cal
Accredited calibration options available



AC Hipot



DC Hipot



Ground Bond



Ground Continuity



Insulation Resistance



Leakage Current



Functional Run



Power Source Recommended

POPULAR MEDTEST CONFIGURATIONS



OMNIA® II 8207 AND SC6540

- All in one testing system (Hipot, Ground Bond, Insulation Resistance, and Leakage Current)
- Built in 500 VA AC power source
- Efficient use of rack space
- SC6540 provides automated multi-point testing
Most common applications incorporate 8 or 16 port multiplexers



OMNIA® II 8206, SC6540 AND POWERED BY AN AC POWER SOURCE

- All in one testing system (Hipot, Ground Bond, Insulation Resistance, and Leakage Current)
- Compatible APT power source provides power to DUT*
Available power ratings: 500 VA – 6 kVA
- SC6540 provides automated multi-point testing.
Most common applications incorporate 8 or 16 port multiplexers

*Choose from APT 300XAC, 7000 or 6000 Series.



OMNIA® II 8204, 620L, SC6540 AND POWERED BY AN AC POWER SOURCE

- All in one testing system (Hipot, Ground Bond, Insulation Resistance, and Leakage Current)
- Compatible APT power source provides power to DUT*
Available power ratings: 500 VA – 6 kVA
- SC6540 provides automated multi-point testing
Most common applications incorporate 8 or 16 port multiplexers
- Up to 40 A continuous current capability for applications that draw greater than 16 A of current

*Choose from APT 300XAC, 7000 or 6000 Series.

LINE CONDITIONS		
Reverse Power Switch	Switch for power polarity reversal	
Neutral Switch	Neutral switch on/off selection for single fault	
Ground Switch	Ground switch on/off selection for class I single fault	
PROBE SETTINGS		
Surface to Surface	(PH – PL)	
Surface to Line	(PH – L)	
Ground to Line	(G – L)	
LEAKAGE LIMIT SETTINGS		
Touch Current High/Low Limit (rms)	Range: Resolution:	0.0 μ A – 999.9 μ A / 1,000 μ A – 9,999 μ A / 10.00 mA – 20.00 mA 0.1 μ A / 1 μ A / 0.01 mA
Touch Current High/Low Limit (Peak)	Range: Resolution:	0.0 μ A -999.9 μ A / 1,000 μ A – 9,999 μ A / 10.00 mA – 30.00 mA 0.1 μ A / 1 μ A / 0.01 mA
MEASURING DEVICE MODULE		
MD1	UL544NP, UL484 , UL923, UL471, UL867, UL697	
MD2	UL544P	
MD3	IEC 60601-1	
MD4	UL1563	
MD5	IEC60990 Fig4 U2, IEC60950-1, IEC60335-1, IEC60598-1,IEC60065, IEC61010	
MD6	IEC60990 Fig5 U3, IEC60598-1	
MD7	IEC60950, IEC61010-1 FigA.2 (2 kohm) for Run function	
External MD	Basic measuring element 1 kohm	
MD Voltage Limit	70 VDC	
DUT POWER		
AC Voltage	0.0 – 277.0 V	
AC Current	40 A max continuous	
AC Voltage High/Low Limit	Range: Resolution:	0.0 – 277.0 V 0.1 V/step
AC Voltage Display	Range: Resolution: Accuracy:	0.0 – 277.0 V 0.1 V/step \pm (1.5% of reading + 2 counts), 30.0 – 277.0 V
Delay Time Setting	Range: Resolution:	0.5 – 999.9 sec 0.1 sec
Dwell Time Setting	Range: Resolution: Accuracy:	0, 0.5 – 999.9 sec (0=Continuous) 0.1 sec \pm (0.1% of reading + 0.05 seconds)
Failure Protection	On Start-Up – Neutral Voltage Check (Neutral – V) Over current and ground current check (Line – OC)	

DIELECTRIC WITHSTAND TEST MODE			
Output Rating*	5 kV @ 50 mAAC 6 kV @ 20 mADC		
Voltage Setting	Range: Resolution: Accuracy:	0 – 5,000 VAC, 0 – 6,000 VDC 1 V ± (2% of setting + 5 V)	
HI and LO-Limit	AC Total	Range: Resolution: Accuracy:	0.000-9.999 mA 0.001 mA ± (2% of setting + 2 counts)
		Range: Resolution: Accuracy:	10.00 – 50.00 mA 0.01 mA ± (2% of Setting + 2 counts)
	AC Real	Range: Resolution: Accuracy:	0.000 – 9.999 mA 0.001 mA ± (3% of setting + 50 µA)
		Range: Resolution: Accuracy:	10.00 – 50.00 mA 0.01 mA ± (3% of setting + 50 µA)
	DC	Range: Resolution: Accuracy:	0.00 – 999.9 µA 0.1 µA ± (2% of setting + 2 counts)
		Range: Resolution: Accuracy:	1,000 – 20,000 µA 1 µA ± (2% of setting + 2 counts)
Ramp HI	> 20 mA peak maximum, ON/OFF selectable		
Charge LO	Range:	0.000 – 350.0 µA or Auto Set	
DC Output Ripple	≤ 4% Ripple rms at 5 kVDC @ 20 mA, Resistive Load		
Discharge Timer	< 50 msec for no load, < 100 msec for capacitor load (All capacitance values in MAX load spec below)		
Maximum Capacitive Load	1 µF < 1 kV 0.75 µF < 2 kV 0.50 µF < 3 kV	0.08 µF < 4 kV 0.04 µF < 6 kV	
Output Frequency	50/60 Hz ± 0.1% , User Selection, 400/800 Hz Option		
AC Output Waveform	Sine Wave, Crest Factor = 1.3 – 1.5		
Output Regulation	± (1% of output + 5 V) from no load to full load and over input voltage range		
Dwell Timer	AC 0, 0.4 – 999.9 sec (0=Continuous) DC 0, 0.3 – 999.9 sec (0=Continuous)		
Ramp Timer	Ramp-Up AC: 0.1 – 999.9 Ramp-Down AC: 0.0-999.9 Ramp-Up DC: 0.4 – 999.9 Ramp-Down DC: 0.0, 1.0-999.9		
Ground Continuity	Current: DC 0.1 A ± 0.01 A, fixed Max. Ground Resistance: 1 Ω ± 0.1 Ω, fixed		
Ground Fault Interrupt	GFI Trip Current: 5.0 mA max HV Shut Down Speed: < 1 ms		

*Output voltage limited to 3.5 kV with 620L option 03

CONTINUITY TEST MODE		
Output Current	DC 0.1 A \pm 0.00001 A	
Resistance Display	Range:	0.00 – 10,000.00 Ω
HI and LO-Limit	0.00 – 10,000 Ω	
Dwell Timer	Range:	0.0, 0.3 – 999.9 sec (0=Continuous)
Milliohm Offset	Range:	0.00 – 10.00 Ω
GROUND BOND TEST MODE		
Output Voltage	Range:	3.00 – 8.00 VAC
Output Frequency	50/60 Hz \pm 0.1%, User Selection	
Output Current	Range: Resolution: Accuracy:	1.00 – 40.00 A 0.01 A \pm (2 % of setting + 2 counts)
Output Regulation	\pm (1% of output + 0.02 A) Within maximum load limits, and over input voltage range	
Maximum Loading	1.00 – 10.00 A, 0 – 600 m Ω 10.01 – 30.00 A, 0 – 200 m Ω 30.01 – 40.00 A, 0 – 150 m Ω	
HI and LO-Limit	Range:	0 – 150 for 30.01 – 40.00 A
	Range:	0 – 200 for 10.01 – 30.00 A
	Range:	0 – 600 for 6.00 – 10.00 A
	Range:	0 – 600 for 5.99 – 1.00 A
	Resolution:	1 m Ω
	Accuracy:	6.00 – 40.00 A, \pm (2% of setting + 2 Counts) 1.00 – 5.99 A, \pm (3% of setting + 3 Counts)
Milliohm Offset	Range:	0 – 200 m Ω
INSULATION RESISTANCE TEST MODE		
Output Voltage	Range:	30 – 1,000 VDC
Charging Current	Maximum > 20 mA peak	
HI and LO-Limit	Range: Resolution:	0.05-99.99 M Ω 0.01 M Ω
	Range: Resolution:	100.0 – 999.9 M Ω 0.1 M Ω
	Range: Resolution:	1000 – 50,000 M Ω 1 M Ω
Charge-LO	0.000 – 3.500 μ A or Auto Set	
Ramp Timer	Ramp Up: Ramp Down:	0.1 – 999.9 secs 0.0, 1.0 – 999.9 secs
Dwell Timer	0, 0.5 – 999.9 (0=Continuous)	
Delay Timer	0.5 – 999.9 secs	
Ground Fault Interrupt	GFI Trip Current: 5.0 mA max HV Shut down Speed: < 1 ms	

GENERAL SPECIFICATIONS	
Interface	Standard: USB, RS-232 Optional: Ethernet, GPIB
Safety	Built-in SmartGFI® circuit
Memory	620L: 50 memories, 30 steps per memory OMNIA® II: 10,000 steps
AC POWER SOURCE	
AC Power Source	Up-to 4 kVA compatible power sources available
Configuration	AC Power Source configuration depends on application. MedTEST hardware is configured for testing products with one side of the supply mains at earth potential (Fig 10 UL60601-1). MedTEST hardware is configured for unbalanced 0-277 V DUT input power. Custom Configurations available. Contact us for details.

Why We Use Counts

Associated Research publishes some specifications using “counts” which allows us to provide a better indication of the instrument’s capabilities across measurement ranges. A count refers to the lowest resolution of the display for a given measurement range. For example, if the resolution for voltage is 1V then 2 counts = 2 V.








Specifications subject to change without notice.

SYSTEMS

Production Line Electrical Safety Compliance in a Convenient Stackable or Rackable Configuration





Interconnect our Hypot® Series Hipot Instrument with our HYAMP® Series Ground Bond instrument to form a complete safety compliance system. Easily operate both instruments from a single point of control on the production line or in a rack. All test systems are safety agency listed, include interconnect cables, and detailed directions on effortlessly interconnecting your system.

	Hypot® 3805  AC Hipot	Hypot® 3865   AC Hipot DC Hipot	Hypot® 3870    AC Hipot DC Hipot Insulation Resistance
HYAMP® 3240  40A Ground Bond	System 32-05	System 32-65	System 32-70




Record, track and store your data with our brand new software as a service.

- Unlimited Users
- Remote Instrument Connection
- Intuitive User Interface
- Immediate Cloud Storage



The platform's interface introduces an intuitive user experience making it easy to setup, run tests and view your reports.



Cloud storage ensures that your tests and data will never be lost or altered – all information is stored immediately to the cloud for access at any time.

► Try it out for yourself with a free 30-day trial. Click [here](#).



Boost Productivity with our Automation & Data Capturing Software


Compatible with OMNIA® II, HypotULTRA®, LINECHEK® II & SC6540

Discover the benefits of Autaware®3 by taking it for a test drive with our **FREE 30 DAY TRIAL**
Visit arisafety.com/autaware3 to download today!



Barcode Capability

Increase production throughput by incorporating a barcode scan. Autaware®3 fully supports direct barcode connection which enables the user to scan model and serial numbers that can be recorded in a data file.



BatchTEST®

Shave minutes off your test routines by testing multiple DUT's simultaneously. Combined with a multiplexer, our BatchTEST® feature performs AC/DC Hipot, Continuity and Insulation Resistance tests on a batch of DUT'S in a convenient 1-step test.

Features and Benefits

Comprehensive Data Capture

Improve tractability and customize test results from multiple workstations anywhere on your network.

DualCHEK® Print Report Functionality

Print Report will show both Ground Bond and ACW/DCW results when DualCHEK® is performed.

Source Code Available

Customize Autaware®3 to fit your needs.

ESSENTIAL WORKSTATION ACCESSORIES

Test Verification Box TVB-2

The TVB-2 is a go/no-go daily test verification box designed to ensure that the failure detectors of an Associated Research electrical safety testing instrument are functioning properly. We designed the TVB-2 to verify Hipot, Insulation Resistance, Ground Bond, and Ground Continuity test functionality. If you perform daily verifications on your testing equipment, then the TVB-2 is an ideal solution. An accessory cord is available to customers who prefer to verify their test instrument using an adapter box.



TVB-2 Accessory Cord 39514

Accessory line cord for the TVB-2 allows convenient connection to a standard adapter box.



Leakage Current Verification Box LVB-2

Verify the failure detectors of your Associated Research Leakage Current Test instrument are functioning properly with this go/no-go load box.



Red/Green Signal Tower Light 39560

Gives an indication as to the status of the testing area. A green light indicates the Hipot instrument is not outputting high voltage and the test area is safe. A red light indicates that the Hipot instrument is active and to stay clear of the test area.



Magnetic Hipot Return Cable CBLSR-05M

Magnetic Ground Bond Return Cable CBLHR-05M



2 Wire 40A Ground Bond Probe 38539

4 Wire 40A Ground Bond Probe 38538



High Voltage Pistol Probe with Switch 38814



High Voltage Probe 38081

Return Probe 38082



Insulation Mat 39539

Dimensions
36" x 36" (914.4 x 914.4mm)



High Voltage Warning Sign 39538



DUT Enclosure Wood Frame with Foam Interior 39067

Protect your operator from electric shock by enclosing your DUT. Our enclosures automatically disable the instrument's output when the enclosure door is opened. Our DUT Enclosures are designed to protect the operator from electric shock during testing. Interface an enclosure with our Remote Safety Interlock feature to automatically disable the instrument's output when the enclosure door is opened.

Outside dimensions (W x D x H): 24" x 19" x 11.5" (610 x 483 x 293 mm)

Inside dimensions (W x D x H): 20" x 16" x 10" (508 x 407 x 254 mm)

3/4" Walls, 3/4" Flame Retardant Foam, 1/4" Plexiglass cover



Dual Palm Remote Switch DPR-01

Prevent your operator from touching a DUT as their hands must stay on the test switches to continue to run a test.




Remote Test Box w/LED Indicators RTB-02

Helps maintain a safe distance between the operator and test instrument when starting and restarting a test. Compatible with all models except SC36540.



E-Stop ESTOP

Immediately stop the flow of electric current to your instrument when the E-Stop is triggered. The E-Stop provides the safest and fastest way for a rescuer to save an operator from injury.



WE WILL HELP MAKE SURE YOUR SYSTEM IS SAFE AND EFFECTIVE

APPLICATIONS CONSULTING

A DIVISION OF IKONIX USA

- Implement best practices
- Validate your test system
- Conform to OSHA requirements



Visit ikonixusa.com/consulting to learn how we can help your team

COMMON SAFETY STANDARD REFERENCE CHART

Standard/ Harmonized Standard	Testing Type	Dielectric Withstand			Ground Bond/Continuity				
		Test Voltage	Max I.	Test Time	Test Current	V Limit	Max. R	Test Time	
IEC/UL 60601-1 3rd Edition Medical Electrical Equipment	Performance	500 – 4000 VAC or 707 – 5656 VDC	No Breakdown	60 s	10-25 A	≤ 6 V	≤ 0.1 Ω	5 s	
	Production*	1000 – 3000 VAC		1 or 60 s	10-25 A	≤ 6 V	≤ 0.1 Ω	5 s	
IEC 61730-2 UL 1703 Photovoltaic Modules & Panels	Performance	1000 VAC + 2 x rated V or 2000 VAC + 4 x rated V	50 uA	60 s	2.5 x Max Over Current Protection	≤ 12 V	≤ 0.1 Ω	120 s	
	Production	1000 VAC + 2 x rated V or (1000 VDC + 2 x rated V) X 120%	50 uA	1 or 60 s	Continuity				
IEC 60335-1 Household Electrical Appliances	Performance	500 – 2400 VAC x rated V + 2400 VAC	No Breakdown	60 s	≥ 10 A	≤ 12 V	0.1 – 0.2 Ω	≤ 120 s	
	Production	400 – 2500 VAC	5-30 mA	1 s	≥ 10 A	≤ 12 V	0.1 – 0.2 Ω	No time specified	
UL 60335-1 Household Electrical Appliances	Performance	500V – 2400 VAC x rated V + 2400 VAC	No Breakdown	60 s	40 A	≤ 6.5 V	≤ 0.5 Ω	120 s	
	Production	400 – 2500 VAC	5-30 mA	1 s	40 A	≤ 12 V	0.1 – 0.2 Ω	No time specified	
IEC 60598-1 Luminaires	Performance	500 – 4 x rated V + 2000 VAC	No Breakdown	60 s	≥ 10 A	≤ 12 V	≤ 0.5 Ω	60 s	
	Production	Not Specified – Responsibility of Manufacturer							
UL 1598 Luminaires	Performance	1000 VAC – 1000 VAC x 2 x rated V	No Breakdown	60 s	30 A	≤ 4 V	≤ 0.1 Ω	120 s	
	Production	1200 VAC		1 s	Continuity		≤ 0.1 Ω	Continuity	
IEC/UL 61010-1 & CSA 22.2 No. 61010-1 Laboratory Control Test & Measurement Equipment	Performance	840 – 11940 VAC or 1200 – 7500 VDC	No Breakdown	5 – 60 s	25 or 30 A	≤ 10 V or ≤ 12 V	≤ 0.1 Ω or < 4 V 0.133 Ω	60 or 120 s	
	Production			5 s max ramp up 2 s dwell	Continuity				
EN 60204-1 Electrical Equipment of Machines	Performance	2 x rated V or 1000 VAC	No Breakdown	1 s	0.2 – 10 A	≤ 24 V	Refer to Section 18.2.2	No time specified	
	Production	Not Specified – Responsibility of Manufacturer							
UL 2202 Electric Vehicle Charging System Equipment	Performance	500 VAC or 1000 VAC + 2 x rated V	No Breakdown	60 s	≤ 60 A	≤ 12 V	Continuity	120 – 240 s	
	Production	1000 – 1700 VAC + 3.4 x rated V		60 or 1 s	Continuity				
IEC 61851-1 Electric Vehicle Conductive Charging System	Performance	1200 VAC + rated V or DC Equivalent	No Breakdown	60 s	Continuity				
	Production	Not Specified – Responsibility of Manufacturer							
UL 45A Portable Electrical Appliances	Performance	1000 VAC + 2 x rated V or DC equivalent	No Breakdown	60 s	Continuity				
	Production	1000 – 3000 VAC		1 s	Continuity				
EN 60950-1 EN 50116 Information Technology Equipment	Performance	1000 – 3000 VAC or 1414 – 4242 VDC	No Breakdown	120 s	30 A	≤ 12 V	≤ 0.1 Ω	60 s	
	Production			1 – 4 s	25 A	≤ 12 V	≤ 0.1 Ω	1-4 s	
UL 60950-1 CSA 22.2 No. 60950-1 Information Technology Equipment	Performance	1000 – 3000 VAC or 1414 – 4242 VDC	No Breakdown	60 s	≤ 40 A	≤ 12 V	≤ 0.1 Ω	60 s	
	Production			1 – 6 s	Continuity				

*As a result of performing risk analysis, many medical device manufacturers are performing leakage tests as part of 100% production line testing.

	Earth Leakage		Insulation Resistance			Suggested Model	Testing Type	Standard/ Harmonized Standard
	Test Voltage	Max I.	Test Time	V Limit	Min. R	AR Instrument		
	110% x rated V	5-10 mA		N/A		8206, 8207, 8256, 8257 or MedTEST	Performance	IEC/UL 60601-1 3rd Edition Medical Electrical Equipment
	110% x rated V	5-10 mA		N/A		7804 or 7854	Production*	
	Max rated V	10 uA – 1 mA	10 uA – 1 mA	500 VDC or Max rated V	40-400 MΩ	3240, 8206, 8207, 8256, 8257 or MedTEST	Performance	IEC 61730-2 UL 1703 Photovoltaic Modules & Panels
	N/A			N/A		3240, 3870 or 7850	Production	
	1.06 x rated V	0.25 – 5.0 uA		N/A		8256 or 8257	Performance	IEC 60335-1 Household Electrical Appliances
	N/A			N/A		7804	Production	
	1.06 x rated V	0.25 – 5.0 uA		N/A		8256 or 8257	Performance	UL 60335-1 Household Electrical Appliances
	N/A			N/A		7804	Production	
	Rated V	0.5 – 10 mA	60 s	500 VDC	1-4 MΩ	8206, 8207, 8256 or 8257	Performance	IEC 60598-1 Luminaires
	Not Specified – Responsibility of Manufacturer					Hypot® or 7850	Production	
	N/A		No time specified	500 VDC	≥ 2 MΩ	7804 or 7854	Performance	UL 1598 Luminaires
	N/A			N/A		Hypot® or 7850	Production	
	< 300 V	0.5 mA		N/A		8256, 8257 or MedTEST	Performance	IEC/UL 61010-1 & CSA 22.2 No. 61010-1 Laboratory Control Test & Measurement Equipment
	N/A			N/A		3865 or 7850	Production	
	N/A		No time specified	500 V	≥ 1 MΩ	7804 or 7854	Performance	EN 60204-1 Electrical Equipment of Machines
	Not Specified – Responsibility of Manufacturer					Hypot® or 7850	Production	
	Rated V	0.5 – 0.75 mA or 5 mA		N/A		8206, 8207, 8256, 8257 or MedTEST	Performance	UL 2202 Electric Vehicle Charging System Equipment
	N/A			N/A		Hypot® or 7850	Production	
	Touch Current Only		60 s	500 V	≥ 1 MΩ or ≥ 7 MΩ	8206, 8207, 8256, 8257 or MedTEST	Performance	IEC 61851-1 Electric Vehicle Conductive Charging System
	Not Specified – Responsibility of Manufacturer					Hypot® or 7850	Production	
	< 300 V	0.5 – 3.5 mA	60 s	500 V	≥ 50 KΩ	8206, 8207, 8256, 8257 or MedTEST	Performance	UL 45A Portable Electrical Appliances
	N/A			N/A		Hypot® or 7850	Production	
	< 300 V	0.25 – 3.5 mA	60 s	500 V	≥ 2 MΩ	8206, 8207, 8256, 8257 or MedTEST	Performance	EN 60950-1 EN 50116 Information Technology Equipment
	N/A			N/A		7804 or 7854	Production	
	< 300 V	0.25 – 3.5 mA	60 s	500 V	≥ 2 MΩ	8206, 8207, 8256, 8257 or MedTEST	Performance	UL 60950-1 CSA 22.2 No. 60950-1 Information Technology Equipment
	N/A			N/A		Hypot® or 7850	Production	



HEADQUARTERS

28105 N. Keith Drive
Lake Forest, IL 60045 USA
Telephone +1-847-367-4077
Fax +1-847-367-4080
Email info@ikonixusa.com



Cal Power

Via Acquanera, 29 22100 COMO
tel. 031.526.566 (r.a.) fax 031.507.984
info@calpower.it www.caltower.it



We Have Local Sales Offices Throughout the World

To find your nearest representative
visit us at arisafety.com