

MICRO-BATHS



Micro-Baths

Models 6102, 7102, and 7103

- World's smallest portable calibration baths
- Calibrates sensors of any size or shape
- Stability to $\pm 0.015^{\circ}\text{C}$
- Ranges from -30°C to 200°C

Need portability and extreme stability? Hart Micro-Baths have both. We invented the Micro-Bath. And, while many have tried to duplicate it, none of them use proprietary Hart Scientific controllers, so none of them deliver performance like a Hart bath. Micro-Baths can be used anywhere for any type of sensor. The Model 6102 weighs less than 10 pounds, with the fluid. It's lighter and smaller than most dry-wells, has a spill-proof lid, and is easier to carry than your lunch. You can take it where you need to go without carts or excessive effort. Micro-Baths can even be transported with the fluid in them.

Wherever you go with your Micro-Bath, you can count on its performance. Each model is stable to $\pm 0.03^{\circ}\text{C}$ or better, depending on the fluid you use. Uniformity is $\pm 0.02^{\circ}\text{C}$ or better for low uncertainties using a reference thermometer. Display accuracy has been improved to

$\pm 0.25^{\circ}\text{C}$ for quick calibrations without a reference thermometer. In short, you get the stability and precision of a liquid bath in a dry-well-sized package. Don't be fooled by competitors who place a can of oil inside a dry-well and call it a bath. Hart Micro-Baths are maximized for true fluid-bath performance.

With a 1.9-inch diameter, 5.5-inch deep tank, a Micro-Bath can calibrate any type of sensor including short, square, or odd-shaped sensors. The problems of fit and immersion are virtually eliminated by using a fluid medium rather than a dry-block calibrator. Micro-Baths are perfect for liquid-in-glass and bimetal thermometers.

The 6102 has a temperature range from 35°C to 200°C , the 7102 covers -5°C to 125°C , and the 7103 extends from -30°C to 125°C . Stability, uniformity, and accu-

racy specifications cover the entire range for each bath, not just the best temperature.

All Micro-Baths have RS-232 ports, come with our Interface-*it* software, and can be used with Hart's MET/TEMP II software (described on page 75). Also included are contacts to calibrate a thermal switch, eight set-point memory storage, ramp-rate adjust, and over-temperature safety cutout.

You may have noticed we haven't touted our CFC-free refrigeration. Yes, cold Micro-Baths are CFC-free, and also compressor-free. That's right—no heavy, noisy compressor to lug around. We achieve our temperature range and stability with only one moving part. This means more durability and less weight.

Hart manufactures and sells temperature calibration baths of every size and shape, and now we have the smallest and lightest baths in the industry to go with the dozens of other models we make.

Look at the specs, price, and value of these portable instruments and you'll know why Hart Scientific is the number-one company in this business.



A Micro-Bath's 1.9-inch-diameter tank lets you calibrate just about any size industrial sensor.



Don't forget a protective case!



See our selection of bath fluids on page 104.

Cal Power

Via Acquanera, 29 22100 COMO
tel. 031.526.566 (r.a.) fax 031.507.984
info@calpower.it www.calspower.it

Ranges from -30°C to 200°C

| Specifications | 6102 | 7102 | 7103 |
|----------------------------|--|---|--|
| Range | 35°C to 200°C (95°F to 392°F) | -5°C to 125°C (23°F to 257°F) | -30°C to 125°C (-22°F to 257°F) |
| Accuracy | ±0.25°C | | |
| Stability | ±0.02°C at 100°C (oil 5013) ±0.03°C at 200°C (oil 5013) | ±0.015°C at -5°C (oil 5010) ±0.03°C at 121°C (oil 5010) | ±0.03°C at -25°C (oil 5010) ±0.05°C at 125°C (oil 5010) |
| Uniformity | ±0.02°C | | |
| Resolution | 0.01°C/F | | |
| Operating Temperature | 5°C to 45°C | | |
| Heating Time | 25°C to 200°C: 40 minutes | 25°C to 100°C: 30 minutes | 25°C to 100°C: 35 minutes |
| Cooling Time | 200°C to 100°C: 35 minutes | 25°C to 0°C: 30 minutes | 25°C to -20°C: 45 minutes |
| Well Size | 2.5" dia. x 5.5" deep (64 x 139 mm) (access opening is 1.9" [48 mm] in diameter) | | |
| Size | 5.5" W x 10.38" H x 8" D (14 x 26 x 20 cm) | 7.2" W x 12" H x 9.5" D (18 x 31 x 24 cm) | 9" W x 13.2" H x 10.5" D (23 x 34 x 26 cm) |
| Weight | 10 lb. (4.5 kg) with fluid | 15 lb. (6.8 kg) with fluid | 22 lb. (9.8 kg) with fluid |
| Volume | 0.75 L | 0.75 L | 1.0 L |
| Power | 115 VAC (±10%), 2.3 A or 230 VAC (±10%), 1.1 A, switchable, 50/60 Hz, 270 W | 115 VAC (±10%), 1.8 A or 230 VAC (±10%), 0.9 A, switchable, 50/60 Hz, 200 W | 94-234 VAC (±10%), 50/60 Hz, 400 W |
| Computer Interface | RS-232 included with free Interface- <i>it</i> software | | |
| NIST-Traceable Calibration | Data at 50°C, 100°C, 150°C, and 200°C | Data at -5°C, 25°C, 55°, 90°C, and 121°C | Data at -25°C, 0°C, 25°C, 50°C, 75°C, 100°C, and 125°C |

Ordering Information - 6102

| | |
|-----------|--|
| 6102 | Micro-Bath, 35°C to 200°C (includes a transport seal lid and a 2082-M test lid) |
| 2082-M | Spare test lid |
| 2083 | 3-inch tank extension adapter (affects stability, uniformity, and range at extreme temperatures) |
| 5013-L | Silicone oil, type 200.20, 1 liter (usable range: 10°C to 230°C) |
| 9310 | Carrying Case |
| 2025-6102 | X Cell Basket (see page 34) |
| 3320 | Spare Stir Bar, MicroBath |

Ordering Information - 7102

| | |
|-----------|--|
| 7102 | Micro-Bath, -5°C to 125°C (includes a transport seal lid and a 2082-P test lid) |
| 2082-P | Spare test lid |
| 2083 | 3-inch tank extension adapter (affects stability, uniformity, and range at extreme temperatures) |
| 5010-L | Silicone oil, type 200.05, 1 liter (usable range: -40°C to 130°C) |
| 9311 | Carrying Case |
| 2025-6102 | X Cell Basket (see page 34) |
| 3320 | Spare Stir Bar, MicroBath |

Ordering Information - 7103

| | |
|-----------|--|
| 7103 | Micro-Bath, -30°C to 125°C (includes a transport seal lid and a 2085 test lid) |
| 2085 | Spare test lid |
| 5010-L | Silicone oil, type 200.05, 1 liter (usable range: -40°C to 130°C) |
| 9317 | Carrying Case |
| 2025-7103 | X Cell Basket (see page 34) |
| 3320 | Spare Stir Bar, MicroBath |



Use MET/TEMP II software and a reference thermometer to recalibrate your own heat sources!



Tim knows the rules—which makes us real glad he's our accountant.

Cal Power

Via Acquana, 29 22100 COMO
tel. 031.526.566 (r.a.) fax 031.507.984
info@calpower.it www.calspower.it